Huang, D., Yu, Z., Li, Y., Han, D., & Chu, Q. (2017). Calculation method and application of loss of life caused by dam break in China. *Natural Hazards*, 85(1), 39-57. <https://doi.org/10.1007/s11069-016-2557-9>

Peer reviewed version

Link to published version (if available):
[10.1007/s11069-016-2557-9](https://doi.org/10.1007/s11069-016-2557-9)

[Link to publication record in Explore Bristol Research](#)
PDF-document

This is the author accepted manuscript (AAM). The final published version (version of record) is available online via Springer at <http://link.springer.com/article/10.1007/s11069-016-2557-9>. Please refer to any applicable terms of use of the publisher.

University of Bristol - Explore Bristol Research

General rights

This document is made available in accordance with publisher policies. Please cite only the published version using the reference above. Full terms of use are available:
<http://www.bristol.ac.uk/red/research-policy/pure/user-guides/ebr-terms/>

Fig. 1 Annual average number of dam break cases in each decade

Fig. 2 Reservoirs locations

Fig. 3 Flow chart of the calculation method of loss of life

Fig. 4 *IFL* filtration in four modules

Fig. 5 Modules results of fourteen reservoirs

Fig. 1 Annual average number of dam break cases in each decade

Fig. 2 Reservoirs locations

Fig. 3 Flow chart of the calculation method of loss of life

Fig. 4 *IFL* filtration in four modules

Fig. 5 Modules results of fourteen reservoirs