Getirana, A., Peters-Lidard, C., Rodell, M., & Bates, P. (2017). Trade-off between cost and accuracy in large-scale surface water dynamic modeling. *Water Resources Research*.
<https://doi.org/10.1002/2017WR020519>

Publisher's PDF, also known as Version of record

Link to published version (if available):
[10.1002/2017WR020519](https://doi.org/10.1002/2017WR020519)

[Link to publication record in Explore Bristol Research](#)
PDF-document

This is the final published version of the article (version of record). It first appeared online via AGU at <http://onlinelibrary.wiley.com/doi/10.1002/2017WR020519/abstract?>. Please refer to any applicable terms of use of the publisher.

University of Bristol - Explore Bristol Research

General rights

This document is made available in accordance with publisher policies. Please cite only the published version using the reference above. Full terms of use are available:
<http://www.bristol.ac.uk/red/research-policy/pure/user-guides/ebr-terms/>

Water Resources Research

RESEARCH ARTICLE

10.1002/2017WR020519

Key Points:

- KINE runs show clear deterioration along main rivers, but is at least 25% more efficient than INER with low model sensitivity to longer dt
- Results show small overall improvement in simulated streamflows with INER and HYBR compared with KINE, but high improvement in water levels
- Combining both KINE and INER formulations, resulting in HYBR, may result in an optimal compromise between efficiency and computational costs

Correspondence to:

A. Getirana,
augusto.getirana@nasa.gov

Citation:

Getirana, A., C. Peters-Lidard, M. Rodell, and P. D. Bates (2017), Trade-off between cost and accuracy in large-scale surface water dynamic modeling, *Water Resour. Res.*, 53, doi:10.1002/2017WR020519.

Received 1 FEB 2017

Accepted 19 MAY 2017

Accepted article online 24 MAY 2017

Trade-off between cost and accuracy in large-scale surface water dynamic modeling

Augusto Getirana^{1,2}, Christa Peters-Lidard¹ , Matthew Rodell¹ , and Paul D. Bates³

¹Hydrological Sciences Laboratory, NASA Goddard Space Flight Center, Greenbelt, Maryland, USA, ²Earth System Science Interdisciplinary Center, University of Maryland, College Park, Maryland, USA, ³School of Geographical Sciences, University of Bristol, Bristol, UK

Abstract Recent efforts have led to the development of the local inertia formulation (INER) for an accurate but still cost-efficient representation of surface water dynamics, compared to the widely used kinematic wave equation (KINE). In this study, both formulations are evaluated over the Amazon basin in terms of computational costs and accuracy in simulating streamflows and water levels through synthetic experiments and comparisons against ground-based observations. Varying time steps are considered as part of the evaluation and INER at 60 s time step is adopted as the reference for synthetic experiments. Five hybrid (HYBR) realizations are performed based on maps representing the spatial distribution of the two formulations that physically represent river reach flow dynamics within the domain. Maps have fractions of KINE varying from 35.6 to 82.8%. KINE runs show clear deterioration along the Amazon river and main tributaries, with maximum RMSE values for streamflow and water level reaching 7827 m³ s^{−1} and 1379 cm near the basin's outlet. However, KINE is at least 25% more efficient than INER with low model sensitivity to longer time steps. A significant improvement is achieved with HYBR, resulting in maximum RMSE values of 3.9–292 m³ s^{−1} for streamflows and 1.1–28.5 cm for water levels, and cost reduction of 6–16%, depending on the map used. Optimal results using HYBR are obtained when the local inertia formulation is used in about one third of the Amazon basin, reducing computational costs in simulations while preserving accuracy. However, that threshold may vary when applied to different regions, according to their hydrodynamics and geomorphological characteristics.

Plain Language Summary Recent efforts have led to the development of the local inertia formulation (INER) for an accurate but still cost-efficient representation of surface water dynamics, compared to the widely used kinematic wave equation (KINE). In this study, both formulations are evaluated over the Amazon basin in terms of computational costs and accuracy in simulating streamflows and water levels through synthetic experiments and comparisons against ground-based observations. Varying time steps are considered as part of the evaluation and INER with a 60-second time step (dt) is adopted as the reference for synthetic experiments. Five hybrid (HYBR) realizations are performed based on maps representing the spatial distribution of the two formulations that minimally represent river reach flow dynamics within the domain. Overall conclusions are: (1) a cost-accuracy tradeoff is observed when choosing between KINE and INER; but (2) hybrid models are a viable alternative that can reduce computational costs in continental and global scale simulations while preserving accuracy, in particular, in representing backwater effects.

1. Introduction

Being able to accurately simulate surface water dynamics is essential for understanding their impacts on regional and global climate and nutrient cycles, determining present and future water availability for human activities and minimizing impacts of extreme events. For these reasons, numerous efforts have led to the development of models and formulations capable of simulating rivers and floodplains at different scales. The Saint-Venant equations, which represent the one-dimensional gradually varied unsteady flow in open channels through simplifications applied to the Navier-Stokes equations, provide the most complete 1-D description of river hydrodynamics. They are based on the mass and the momentum conservation laws, respectively, as follows [Cunge *et al.*, 1980]:

$$\frac{\partial Q}{\partial x} + \frac{\partial A}{\partial t} = 0, \quad (1)$$

$$\frac{\partial}{\partial x} \left[\frac{Q^2}{A} \right] + \frac{\partial Q}{\partial t} + gA \frac{\partial h}{\partial x} = gAi_o - gAi_f, \quad (2)$$

(i) (ii) (iii) (iv) (v)

where Q [$\text{m}^3 \text{s}^{-1}$] is streamflow, t [s] is time, x [m] is river longitudinal space coordinate, h [m] is river water depth, g [m s^{-2}] is acceleration due to gravity, A [m^2] is the cross-sectional flow area perpendicular to the flow direction and i_o [m m^{-1}] and i_f [m m^{-1}] are the bed slope and friction slope in the x direction. The momentum conservation law [equation (2)] is composed of the balance of (i) convective and (ii) local inertia with (iii) pressure, (iv) gravity, and (v) friction forces.

While studies have demonstrated the feasibility of implementing the full Saint-Venant equations at regional scales [e.g., Paz *et al.*, 2011; Paiva *et al.*, 2013], the nonnegligible increase of computational costs and input data constraints are still limiting factors for their implementation globally. In order to avoid these limitations, continental and global-scale river routing schemes have been developed based on simplified relationships between water volume storage within a river reach and its outflow [Vorosmarty *et al.*, 1989; Lohmann *et al.*, 1996; Oki and Sud, 1998; Arora *et al.*, 1999], the Muskingum method and variations [Collischonn *et al.*, 2007; David *et al.*, 2011; Getirana *et al.*, 2014a], the kinematic wave (KINE) [Decharme *et al.*, 2012; Getirana *et al.*, 2012; Li *et al.*, 2015], and diffusive wave (DIFF) [Yamazaki *et al.*, 2011; Luo *et al.*, 2017] methods. Such models have been useful in land surface model (LSM) evaluation [e.g., Getirana *et al.*, 2014a, 2014b, 2014c, 2015, 2017], anthropogenic impacts on the water cycle [Haddeland *et al.*, 2006; Hanasaki *et al.*, 2006; Döll *et al.*, 2009; Biemans *et al.*, 2011], data assimilation experiments [e.g., Kumar *et al.*, 2015, 2016], and global water budget accounting [Clark *et al.*, 2015], among other applications. Most of existing global-scale river routing schemes, in particular those coupled with general circulation models, still use KINE or more basic formulations [e.g., Miller *et al.*, 1994; Decharme *et al.*, 2012], insuring a low computational cost while providing spatial and temporal freshwater discharges from continents into the oceans accurate enough for climate modeling purposes.

More recently, Bates and De Roo [2010] and de Almeida *et al.* [2012] suggested a new explicit solution for the Saint-Venant momentum equation only neglecting the convective term (i). Compared to DIFF, it includes the local inertia term (ii), improving numerical stability and allowing simulations with longer time steps. The local inertia formulation (INER) has been implemented in the Catchment-Based Macro-scale Floodplain (CaMa-Flood) [Yamazaki *et al.*, 2011] river routing scheme and evaluated globally [Yamazaki *et al.*, 2013]. Yamazaki *et al.* compared the new formulation against DIFF in terms of numerical stability, and streamflow and water level simulations at selected gauges. Conclusions were that INER was capable of running global experiments at longer time steps while keeping numerical stability. The authors discuss how computational costs can be improved in further large-scale applications, but no quantitative information is provided.

Although synthetic and small-scale experiments are the most common way to quantitatively compare flood modeling techniques [e.g., Bates and De Roo, 2000; Bates *et al.*, 2010], comprehensive trade-off evaluations in terms of cost and accuracy at the large scale are not commonly found in the literature. Additionally, to date, no detailed comparison between INER and KINE has been undertaken, and this therefore is the objective of this paper. Both formulations have been implemented in the Hydrological Modeling and Analysis Platform (HyMAP) [Getirana *et al.*, 2012] and are evaluated here using synthetic experiments and comparisons against observations over the Amazon basin. Experiments are designed with varying time steps, and efficiency is evaluated in terms of computational costs and accuracy in simulating streamflows and water levels.

Moussa and Bocquillon [1996] initially proposed a method that analyzes flows using Saint-Venant equations as the superposition of a permanent regime and a perturbation of the steady uniform flow. Getirana and Paiva [2013] adapted the technique to map flood wave types at the large scale and evaluated it over the Amazon. They also highlighted the importance of using such maps in the development of models combining multiple formulations in order to minimize computational costs, but preserving accuracy. Indeed, combining methods with different levels of complexity has been a common practice in flood modeling to

optimize computational costs. For example, *Paiva et al.* [2013] coupled the Muskingum-Cunge method [Cunge et al., 1980] and the full Saint-Venant equations in order to simulate the upper Amazon basin. Following that direction, a hybrid model (HYBR), combining both the kinematic wave equation and local inertia formulation, is also implemented in HyMAP and evaluated in this study. Although we acknowledge the existence of numerous flood modeling techniques, such as those listed earlier in the text, and also analytical solutions of the kinematic wave equation [e.g., *Reggiani et al.*, 2014], we limited this comparison to the numerical solutions of KINE, INER, and HYBR. This decision is based on the consideration that the kinematic wave and the local inertia formulation are both physically based and represent extremes of the simplification spectrum of the full Saint-Venant equations.

2. The HyMAP Global-Scale River Routing Scheme

HyMAP is a global-scale river routing scheme composed of the following modules: (1) surface runoff and base flow time delays, (2) river-floodplain interface, (3) flow in both river channels and floodplains, and (4) evaporation from floodplains.

The temporal change of water storage in rivers and floodplains of a grid cell, S , is defined by the continuity equation [equation (3)] considering LSM-based total runoff (after passing through time delay reservoirs), Q_c , river, and floodplain discharges to the downstream grid point, Q^r and Q^f , and from the upstream grid points, Qup^r and Qup^f , and evaporation from open waters (i.e., rivers and floodplains), E ,

$$S_{t+dt} = S_t + \left[Q_c + \sum_{k=1}^{nUp} \left(Qup_t^{r,k} + Qup_t^{f,k} \right) - Q_t^r - Q_t^f - E_t^r \right] dt, \quad (3)$$

where subscripts r and f represent river channel and floodplain variables, respectively. dt stands for time step and the index k the nUp upstream grid cells of the target grid point.

Time delays are represented in HyMAP at the subgrid scale where, in each grid cell, both surface runoff and base flow derived from LSMs pass through individual linear reservoirs with appropriate time delay factors. The current HyMAP parameterization for the Amazon basin considers the base flow time delay as 45 days. The surface runoff time delay T_s is computed for each grid cell following the *Kirpich's* [1940] formula:

$$T_s = 3600 \left(0.868 \frac{\Delta x^3}{\Delta h} \right)^{0.385}, \quad (4)$$

where Δx [km] is the distance between the farthest point within a grid cell and its outlet, and Δh [m] is the difference between the maximum and minimum elevations of the pathway. This formula was initially developed for small agricultural areas, but has been satisfactorily applied to larger regions [e.g., *Collischonn et al.*, 2007; *Getirana et al.*, 2014a]. Both linear reservoir outputs total the discharge produced in each grid cell, Q_c [$m^3 dt^{-1}$], flowing to the river network.

Water overflows to floodplains when the river channel water height h_r [m] is higher than the bank height, H . This process is considered instantaneous at each time step. This means that water surface elevations of the river channel and the floodplain are the same. Elevation profiles are used to represent floodplains. As a result, floodplain water extent and storage can be derived from the floodplain water elevation, h_f .

The river and floodplain water exchange at each time step is represented as follows:

$$\begin{aligned} S_{t+dt}^r &= S \\ \text{if } S_{t+dt} \leq S^{\max} : \quad & \begin{aligned} h_{t+dt}^r &= S_{t+dt}^r / (W \cdot L) \\ S_{t+dt}^f &= 0 \\ h_{t+dt}^f &= 0 \end{aligned} \end{aligned} \quad (5)$$

$$\begin{aligned}
 S'_{t+dt} &= S_{t+dt} - S^f_{t+dt} \\
 h'_{t+dt} &= S'_{t+dt} / (W \cdot L) \\
 \text{else : } S^f_{t+dt} &= \int_0^{A^f_{t+1}} [h^f_{t+dt} - h(A^f_{t+dt})] dA, \\
 h^f_{t+dt} &= h'_{t+dt} - H
 \end{aligned} \tag{6}$$

where S [m^3] stands for the total water storage in the grid cell, S_r [m^3] and S_f [m^3] the river channel and floodplain water storages, h_r [m] and h_f [m] river water depths, W [m] the river width, L [m] the river length, and A_f [m^2] the flooded area. $S_{r \max}$ [m^3] stands for the river bankfull water storage, and is given as $S_{r \max} = H \times W \times L$, where H [m] is the river bankfull height.

Using the kinematic wave equation, considering a rectangular river cross section and large width-to-depth ratio, water discharge through a grid cell river reach at time step $t + dt$, Q_{t+dt} [$\text{m}^3 \cdot \text{s}^{-1}$], can be defined as

$$Q_{t+dt} = \frac{1}{n} \cdot i_0^{1/2} \cdot W \cdot h_t^{5/3}, \tag{7}$$

where n is the Manning roughness coefficient. i_0 is derived from topographic information and corresponds to the slope between the target and downstream grid cells. A minimum i_0 threshold of 10^{-5} m m^{-1} is used in order to avoid negative or very small topography slope caused by DEM errors.

Following the explicit solution presented in *Bates et al.* [2010] and improved in *de Almeida et al.* [2012], the local inertia formulation, for the same river cross sections defined above, can be defined as

$$Q_{t+dt} = \frac{Q_t + g \cdot h_t \cdot dt \cdot i_f}{\left(1 + g \cdot dt \cdot n^2 \cdot |Q_t| / h_t^{10/3}\right)}. \tag{8}$$

For HyMAP to be run in hybrid mode, a map determining the spatial distribution of flow types has to be provided.

In HyMAP, rivers and floodplains flow independently from a grid cell to another and have their hydrodynamics calculated separately using their own channel characteristics, but the same equations. At each time step, the average floodplain width, depth, and bed height are defined as

$$\bar{W}_f = \frac{A_f}{L}, \tag{9}$$

$$\bar{h}_f = \frac{S_f}{A_f}, \tag{10}$$

$$\bar{z}_f = z_r + h_r - \bar{h}_f. \tag{11}$$

For the kinematic wave equation, i_0 is considered the same for both rivers and floodplains. River width W and bankfull height H are both defined based on empirical relationships with long-term average discharges, and the Manning coefficient of river channels n_r varies as a function of H . The Manning coefficient for floodplains, n_f , is spatially distributed as a function of vegetation types derived from a static map [*Masson et al.*, 2003], where larger values correspond to dense vegetated areas and lower values to sparser vegetated regions. More details on HyMAP parameterization are found in *Getirana et al.* [2012, 2013].

2.1. Optimal Time Step for Numerical Stability

The Courant-Freidrichs-Levy (CFL) condition is used in order to determine the optimal time step for numerical stability for INER,

$$C_r = \frac{V \partial t}{\partial x}, \tag{12}$$

where C_r stands for the nondimensional Courant number and V is a characteristic velocity [m s^{-1}]. Numerical stability is obtained when C_r is less than 1. V can be defined for the local inertial form of the shallow water equations as [*Bates et al.*, 2010],

$$V = \sqrt{gh}. \quad (13)$$

Equation (12) can be rewritten as follows, defining the maximum time step needed to keep numerical stability:

$$dt_{\max} = \alpha \frac{dx}{\sqrt{gh_t}}, \quad (14)$$

where α is a coefficient that is used to ensure that the selected time step remains at all times smaller than the maximum threshold for stability. Equation (14) has been implemented in HyMAP to determine optimal time intervals and α was set as 0.9 for all experimental runs (i.e., the actual time step used is 90% of the theoretical maximum).

3. Experimental Design

Experiments are designed with the following objectives: (i) to quantify the gains of using the more complex INNER formulation over the simplified KINE, in terms of accuracy in simulating water levels and streamflows; (ii) to evaluate the sensitivity of both formulations to model time steps; and (iii) to determine the added value in considering a hybrid model HYBR that combines both formulations.

The evaluation is performed in terms of accuracy and computational costs and is composed of two stages: (1) synthetic experiments and (2) evaluation against observations. In stage 1, model accuracy is quantified using the root mean square error (RMSE) against a control simulation. Computational costs are determined in terms of time needed to run the model (excluding initialization and input/output processing). Synthetic experiments are based on the Amazon basin and performed for 2 years (1999–2000), after a 1 year spin-up. The same initial condition is used in all experiments. The INNER experiment at 60 s time step is considered as the control simulation for synthetic experiments, as will theoretically be the highest quality simulation, and the evaluation is performed in terms of streamflows and river water depths/water elevations. In order to evaluate the sensitivity to time steps, five realizations are performed for INNER and KINE, and the following intervals considered: 60, 120, 300, 600, and 1200 s. For consistency, intervals are fixed for each run. This means that $dt_{\max}$ is computed for each run with equation (14), but not used to constrain time steps.

Although ocean tides play an important role in river dynamics near the outlet, they have been neglected in this study. Thus, the downstream boundary water elevation at the Amazon River mouths is set to zero meters constant over time.

Figure 1. Location of radar altimetry and in situ gauges used in the model evaluation. The location of Óbidos (black triangle) and six radar altimetry stations (black circles) mentioned in the discussion are highlighted.

In stage 2, the evaluation against observations has been performed for the 2002–2008 period using daily ground-based streamflow observations at 144 gauges and satellite-based water elevations at 396 locations (see Figure 1 for locations). Runs have been performed at a 15 min time step. Streamflow gauges are operated by the Brazilian Water Agency (*Agência Nacional de Aguas* [ANA]) and the water elevation data set was derived from the Envisat satellite and is available on the Hydroweb website [Cre-taux *et al.*, 2011]. Envisat operated from 2002 to 2010 at a 35 day cycle and absolute water elevation errors within the Amazon

basin are on the order of tens of centimeters [Da Silva et al., 2011].

Daily streamflow is evaluated using the Nash-Sutcliffe (NS) coefficient,

$$NS = 1 - \frac{\sum_{t=1}^{nt} (y_t - x_t)^2}{\sum_{t=1}^{nt} (y_t - \bar{y})^2}, \quad (15)$$

where t is the time step, and nt represents the total number of days with observed data. The variables x and y are, respectively, the simulated and observed signals at time step t , while y_{max} , y_{min} , and $\bar{y}$ represent the respective maximum, minimum, and mean values of the target signals for the entire period. NS ranges from $-\infty$ to 1, where 1 is the optimal case, while zero means that simulations represent observed signals as well as the average of observations. NS of anomalies (NSA) is used to evaluate bias-corrected river water depth simulations against satellite-based water elevations [Getirana et al., 2013]. Bias correction was performed as a solution to eliminate datum differences and eventual errors in the DEM, satellite observations, riverbed height estimates and river width. NSA is defined as follows:

$$NSA = 1 - \frac{\sum_{t=1}^{nt} [(y_t - \bar{y}_t) - (x_t - \bar{x}_t)]^2}{\sum_{t=1}^{nt} (y_t - \bar{y}_t)^2}, \quad (16)$$

where $\bar{x}$ stands for the mean value of the simulated signal for the entire period.

HyMAP runs over the Amazon basin at 0.25° spatial resolution and simulations were performed using a single 2.6 GHz Intel Xeon Haswell processor on the NASA Center for Climate Simulation's Discover system. Daily surface runoff and base flow were derived from a long term run using the Noah 3.3 LSM [Ek et al., 2003] forced with the Princeton University meteorological data set [Sheffield et al., 2006], with a rescaled precipitation matching the ORE-HYBAM (Observatoire de Recherche en Environnement - Hydrologie du Bassin de l'Amazonie) [Guimberteau et al., 2012] data set. Details on the LSM run can be found in Getirana et al. [2014b]. All model runs were executed in the NASA Land Information System (LIS) [Kumar et al., 2006].

4. Results and Discussion

4.1. Synthetic Experiments

According to results presented in Figure 2, KINE satisfactorily represents the hydrodynamics in most of the basin, with low RMSE values for both river water depth and streamflow simulations. However, a significant deterioration of these variables along the Amazon River and main tributaries is observed, as represented by the darker colors in the figures. This deterioration is more evident near the basin's outlet, which could be due to the incapacity of KINE to represent backwater effects. In terms of river water depths, KINE at $dt = 60$ s results in mean RMSE values of ~ 19 cm, relative to INER at $dt = 60$ s, with a maximum value

Figure 2. Root mean square error (RMSE) spatial distribution derived from kinematic wave equation experiments at variable time steps (dt), from 60 to 10,800 s, for river water depths (top) and streamflows (bottom).

Figure 3. Root mean square error (RMSE) spatial distribution derived from local inertia formulation experiments at variable time steps (dt), from 120 to 1200 s, for river water depths (top) and streamflows (bottom).

reaching ~ 1379 cm. Average and maximum RMSE values for streamflows are ~ 52 and ~ 7827 m³ s⁻¹, respectively.

In terms of time step impacts on model accuracy, even though KINE runs result in deteriorated RMSE values over main rivers, additional realizations confirm the low model sensitivity to longer dt, resulting in very similar coefficient values for river water depths and streamflows. For example, mean RMSE values for simulations at dt = 10,800 s are 19.93 cm and 52.97 m³ s⁻¹, respectively. This represents nominal degradations of 3.6 and 1.3%, compared to the experiment at dt = 60 s. Realizations performed with INER show that time steps up to 900 s result in gradual, but still nominal, changes in RMSE values for both variables, as shown in Figure 3. The INER realization at 1200 s time step presents nonnegligible deterioration, mostly occurring in the lower and central Amazon and Negro Rivers, and lower Madeira River. On the other hand, INER in CaMa-Flood is stable at that time step and spatial resolution [Yamazaki *et al.*, 2013]. In that sense, further investigation was carried out in order to identify the reason why such a limitation occurs in HyMAP. Similar simulations considering static floodplains (i.e., no flow in floodplain from a grid cell to another) were performed in order to determine the sensitivity of such a configuration to time step. As a result, it was verified that simulations with static floodplains are stable with dt ≤ 1800 s, meaning that the deterioration observed in INER runs at 1200 s are due to numerical instability caused by more restrictive CFL conditions in the floodplain dynamics. Indeed, this empirical result matches with the CFL condition, computed for the whole experimental period, which shows that the maximum stable time step for HyMAP runs over the Amazon at 0.25° using the local inertia formulation and floodplain dynamics is 1200 s. It is worth noting that HyMAP and CaMa-Flood use different river network parameterizations and that difference may play a major role in computing optimal time steps.

Computational costs for running HyMAP for 2 years are linearly proportional to the number of time steps used in the realizations. INER costs varied from 1017 s at dt = 60s to 51 s at a dt = 1200 s (see Table 1 for computational cost and accuracy summary). This is 25% longer than the corresponding realizations with KINE (812 and 41 s, respectively). However, since the kinematic wave shows low sensitivity to longer time steps, one could obtain similar errors with time steps as long as 10,800 s (or more), as shown in Table 1. This means that significantly cheaper runs (at least 15 times faster) can provide outputs with the same margin of error. At dt = 900 s (the longest time step for INER with demonstrated stability), the mean RMSE for bias-corrected river water depths is 0.03 cm, with a maximum value of 0.5 cm. For streamflows, values are 0.17 and 62.3 m³ s⁻¹, respectively, which are nominal compared to the absolute numbers of each variable.

Flow-type maps applied to HYBR were generated based on absolute values of differential RMSE ($|\Delta rmse| = |rmse_{INER} - rmse_{KINE}|$) between KINE and INER at dt = 60 s. Five $|\Delta rmse|$ thresholds were considered in order to determine their spatial distribution: 1, 5, 10, 15, and 20 cm. These values represent a good flow-type distribution spectrum for HYBR. Figure 4 shows maps with the spatial distribution of different flow

Table 1. Synthetic Experimental Design Overview^a

Equation	Time Step [s]	Computational Cost [s]	Mean RMSE for Water Level [cm]	Mean RMSE for Streamflow [m ³ s ⁻¹]
Local inertia	60	1018.3	0	0
Local inertia	120	506.0	0.01	0.22
Local inertia	300	205.7	0.03	0.28
Local inertia	600	102.7	0.06	0.41
Local inertia	900	68.7	0.09	0.55
Local inertia	1,200	51.3	1.42	26.31
Kinematic wave	60	809.7	19.22	52.27
Kinematic wave	120	412.1	19.22	52.30
Kinematic wave	300	163.3	19.23	52.28
Kinematic wave	600	82.4	19.23	52.26
Kinematic wave	900	55.1	19.24	52.25
Kinematic wave	1,200	41.0	19.25	52.24
Kinematic wave	1,800	27.2	19.27	52.23
Kinematic wave	3,600	13.7	19.34	52.24
Kinematic wave	7,200	6.8	19.57	52.37
Kinematic wave	10,800	4.6	19.93	52.97
Hybrid ($ \Delta rmse \leq 1$ cm)	60	962.6	0.12	0.10
Hybrid ($ \Delta rmse \leq 5$ cm)	60	902.9	0.84	1.12
Hybrid ($ \Delta rmse \leq 10$ cm)	60	883.1	1.64	2.47
Hybrid ($ \Delta rmse \leq 15$ cm)	60	874.5	2.33	3.79
Hybrid ($ \Delta rmse \leq 20$ cm)	60	858.1	2.91	5.30

^aComputational costs are for 2 years of simulation and RMSE values are averages for the whole basin, computed relative to INER outputs at $\Delta t = 60$ s.

types and their respective fractions within the Amazon basin. As shown in the figure, the fraction of pixels within the basin being represented by the kinematic wave equation (f_{KINE}) exponentially increases with $|\Delta rmse|$ threshold limits. f_{KINE} covers 35.6% of the basin if the threshold is 1 cm (i.e., $|\Delta rmse| \leq 1$ cm is considered as an acceptable error), mostly representing headwater grid cells. The fractions increase to 63.5% for 5 cm and to 82.8% for 20 cm.

The local inertia formulation is not as used over the basin when thresholds increase, except along main rivers and main tributaries. Computational costs are linearly related to f_{KINE} , varying from 858.1 to 962.6 s (in comparison to 1018.3 and 809.7 s for INER and KINE, respectively). As shown in Figure 5, mean RMSE values vary from 0.12 to 2.91 cm for river water depths and from 0.10 to 5.30 m³ s⁻¹ for streamflows, demonstrating a significant improvement in accuracy when compared to KINE.

Figure 6 shows the Amazon River water elevation profile, from its headwater to the outlet, simulated with INER, and errors using KINE and HYBR composed of four flow-type maps ($|\Delta rmse|$ thresholds at 1, 5, 10, and 20 cm). Errors use the INER run as the reference. Profiles are averaged for two seasons: austral fall (April–June, or AMJ), and spring (October–December, or OND). The selected periods, respectively, coincide with the high (or humid season) and low (dry season) water discharge periods at the outlet. RMSE values for KINE are 4.94 m for AMJ and OND, respectively. High inaccuracy is observed in flat central and lower parts of the river, where both the pressure force and inertia are more predominant. In the steep upper part of the river, gravity and friction forces mainly control flow dynamics, hence KINE results in much lower errors. It is

Figure 4. Flow-type maps within the Amazon basin based on $|\Delta rmse|$ thresholds. White and black represent areas simulated using the kinematic wave equation and the local inertia formulation, respectively.

Figure 5. Root mean square error (RMSE) spatial distribution derived from hybrid model experiments at $dt = 60$ s and variable $|\Delta rmse|$ thresholds, from 1 to 20 cm, for river water depths (top) and streamflows (bottom).

worth noting the backwater effect in the lower part of the river in terms of absolute errors. During the dry season, higher water elevations due to the ocean's backwater effect are represented with INER. On the other hand, KINE neglects this effect, resulting in lower water elevations represented by the negative errors, as shown in the figure.

Amazon River water elevations simulated by HYBR show significantly lower errors when compared to KINE. RMSE values vary from 4.3 cm ($|\Delta rmse| \leq 1\text{cm}$) to 6.5 cm ($|\Delta rmse| \leq 20\text{cm}$) for AMJ, and from 2.1 to 3.4 cm during the OND period. It is observed that errors occur in the upstream region, where the kinematic wave

Figure 6. Average water elevation profile of the Amazon River for Austral Fall (AMJ) and Spring (OND) averages (1999–2000 period) simulated by the local inertia formulation (top), and errors, relative to the local inertia experiment, resulting from the kinematic wave equation (middle) and the hybrid model composed of four flow-type maps with $|\Delta rmse|$ thresholds at 1, 5, 10, and 20 cm (bottom).

equation is used. That error is not noticeable in KINE due to the much larger scale used to show its results. There is also a nominal error along the central and lower parts of the river (slightly positive and negative for AMS and OND, respectively), explained by the error propagation from the mainstream headwaters and other tributaries.

4.2. Evaluation Against Ground and Satellite Observations

According to Figure 7, NS values are usually higher in the main rivers and deteriorate near headwaters. This is mostly caused by inaccuracies in both the meteorological forcings and LSM transfers to the river routing scheme, as previously discussed in *Getirana et al.* [2014b]. Comparisons between daily streamflow simulations and observations at 144 gauges show a slight improvement of 0.01 in the mean NS in the realization using INER. However, differences are variable across the basin. At Óbidos, the station draining most of the Amazon basin, located about 800 km upstream from the river mouth, NS values using KINE, INER, and HYBR are 0.90, 0.91, and 0.91, respectively. In general, both INER and HYBR performed better in the mainstream, and lower parts of Tapajos, Madeira, and Purus Rivers. Streamflows derived from HYBR do not show any significant change compared to INER. Such a small average difference of NS is mostly due to the fact that daily time series of streamflow observations are only available where backwater effects are minor or nonexistent. This is explained by the fact that such a variable is derived from rating curve relations where the actual observable variable is river water depth, and that rating curves are only efficiently applicable in steady flow regimes [Fenton et al., 2001].

Unlike streamflow observations, radar altimetry enables evaluation of surface water dynamics at any location where satellite tracks intersect water bodies. The 396 radar altimetry stations cover most of the Amazon River and main tributaries, providing us with a detailed picture of how the different methods compare against each other in terms of simulated river water depths. NSA coefficients for river water depths are significantly improved throughout the basin when INER is used compared to KINE (see Figure 8). The average improvement in NSA is 0.37, with differences mostly present near outlets and confluences, as expected. HYBR, with 64% represented as kinematic wave equation, results in similar performance coefficients to INER, with a differential NSA of 0.37. This reaffirms the efficiency of a hybrid model in reducing computational costs and keeping relatively high metrics in terms of both streamflows and river water depths.

It is also observed that some locations resulted in efficiency deterioration (negative differential NS and NSA) for both INER and HYBR when compared to KINE. Plausible explanations for such deterioration could be errors in meteorological forcings, limited representations of physical processes in LSMs that are transferred to the river routing scheme. This error transfer may result in random improvements when combined with river routing scheme errors (i.e., errors in the DEM and river geometry parameters). Errors are also explained by both numeric limitations in HyMAP and inaccuracy in the observed data.

Figure 9 shows bias-corrected daily water elevation time series at the six radar altimetry stations indicated in Figure 1. Bias values are listed in Table 2 for each location and experiment. Stations were intentionally

Figure 7. Nash-Sutcliffe (NS) coefficients of daily streamflows at 144 gauges within the Amazon basin: absolute values using the kinematic wave equation (left); and the differences between the kinematic wave and local inertia formulation (center) and the hybrid model (right).

Figure 8. As Figure 7, but for Nash-Sutcliffe coefficients of river water depth anomalies (NSA) at 396 locations within the Amazon basin.

selected near outlets and confluences in order to expose the improvements obtained using INER. Selected stations are located in the (1) Amazon, (2) Xingu, (3) Tapajos, (4) Madeira, and (5) Negro Rivers, and (6) the Solimões near its confluence with the Negro River.

Improvements obtained with both INER and HYBR are clearly noticed at all selected radar altimetry stations. In particular, at station 1, located near the Amazon River outlet, where river flow is highly impacted by the ocean level, both resulted in smoothed water level changes, agreeing with satellite observations. On the other hand, KINE fails in properly simulating water level amplitudes. NSA coefficients are 0.91 for the first two experiments, and -6.50 for KINE. Similar behaviors are noticed at other stations, where INER and HYBR resulted in attenuated amplitudes relative to observations. At station 5, both experiments show improvements in the peak amplitude and timing, when compared to KINE, resulting in an NSA increase from 0.11 to 0.73. Although improvements are clear, it is noticeable that INER still fails in representing observed

Figure 9. Water elevation derived from Envisat and simulated by HyMAP using the kinematic wave equation (KINE), the local inertia formulation (INER) and the hybrid model (HYBR) at $|\Delta \text{rmse}| \leq 5$ cm. Simulated water elevations are bias-corrected to match the Envisat mean. The locations are shown in Figure 1.

Table 2. Bias Correction in Meters Applied to Simulated Water Elevations at Each of the Six Selected Locations Shown in Figures 1 and 9^a

Location	KINE	INER/HYBR
1 (Amazon)	9.32	3.61
2 (Xingu)	1.70	1.05
3 (Tapajos)	3.52	2.64
4 (Madeira)	10.35	8.31
5 (Negro)	10.20	6.13
6 (Solimões)	9.05	10.19

^aINER and HYBR outputs have the same bias corrections.

reduced computational costs. The development of more sophisticated river flow modeling methods, such as the local inertia formulation, has allowed the scientific community to more accurately represent surface water dynamics. Global applications of such new formulations are feasible, but increased computational costs limit the spatial and temporal resolutions. This study evaluates the latter method compared to the kinematic wave equation in terms of precision and computational costs. It also proposes a hybrid model composed of both formulations, where costs can be reduced, maintaining a high accuracy. The spatial distribution of methods in the hybrid model is determined as a function of differential water level RMSE values between INER and KINE runs at 60 s time step, based on the principle that river dynamics can be numerically represented by the Saint-Venant equation in a satisfactory way at different levels of complexity determined by dominant flow characteristics [Moussa and Bocquillon, 1996]. The evaluation was performed over the Amazon basin in terms of streamflow and water levels and was composed of two steps: (1) accuracy and cost evaluation through synthetic experiments and (2) comparison against in situ and satellite observations. Synthetic experiments considered INER at $dt = 60$ s as the reference, and comparisons against observations used 15 min time step runs.

KINE runs result in large RMSE values along the Amazon River and main tributaries, in particular near the basin's outlet, but these simulations are at least 25% cheaper than the local inertia formulation. INER is numerically stable at time steps lower than 20 min. At that time step, a more restrictive CFL condition imposed by the floodplain dynamics limits HyMAP run numerical stability. This is confirmed with the additional adaptive time step run using the CFL condition. On the other hand, KINE shows low model sensitivity to longer time steps, as expected, allowing dt as large as 3 h with nominal impacts on accuracy. Accuracy was significantly improved with HYBR when compared to KINE, in cases where the local inertia formulation is used in about one third of the basin, with nominal computational cost increase.

Comparisons against in situ and satellite observations show a small overall improvement in simulated streamflows when either INER or HYBR are used, but a significant improvement in water level along main river and tributaries. A possible explanation for such differences in performances is the limited availability of streamflow observations in locations where backwater effects are dominant.

Overall, there is a trade-off between KINE and INER, and users should choose between accuracy (particularly in locations with predominately diffusive hydraulic processes, such as flat areas) and computational cost. However, combining both the kinematic wave and the local inertia formulations based on flow-type maps may result in an optimal compromise between efficiency and computational costs. It is worth noting that the computational cost for runs shown in Table 1 are generally low due to the domain size, spatial resolution, and timespan. In particular, costs increase exponentially with increasing spatial resolutions. Long-timespan high-resolution global runs would require a much higher computer power and the additional computational cost could be a critical factor in determining which method to be used. Finally, considering that using the kinematic wave equation with longer time steps can minimize computational costs preserving numerical stability, future developments could focus on more cost-efficient hybrid models, where spatially distributed time steps would be based on flow types.

References

- Arora, V. K., F. H. S. Chiew, and R. B. Grayson (1999), A river flow routing scheme for general circulation models, *J. Geophys. Res.*, 104(D12), 14,347–14,357.
- Bates, P. D., and A. P. J. De Roo (2000), A simple raster-based model for flood inundation simulation, *J. Hydrol.*, 236(1–2), 54–77.

Acknowledgments

The study benefited from data made available by the Brazilian Water Agency (Agência Nacional de Aguas [ANA]). Radar altimetry data were acquired through the Hydroweb database (<http://www.legos.obs-mip.fr/soa/hydrologie/hydroweb/>). Surface runoff and base flow used to force HyMAP are available under request by contacting Augusto Getirana.

- Bates, P. D., M. S. Horritt, and T. J. Fewtrell (2010), A simple inertial formulation of the shallow water equations for efficient two-dimensional flood inundation modeling, *J. Hydrol.*, *387*, 33–45, doi:10.1016/j.jhydrol.2010.03.027.
- Biemans, H., I. Haddeland, P. Kabat, F. Ludwig, R. Hutjes, J. Heinke, W. von Bloh, and D. Gerten (2011), Impact of reservoirs on river discharge and irrigation water supply during the 20th century, *Water Resour. Res.*, *47*, W03509, doi:10.1029/2009WR008929.
- Clark, E. A., J. Sheffield, M. T. van Vliet, B. Nijssen, and D. P. Lettenmaier (2015), Continental runoff into the oceans (1950–2008), *J. Hydrometeorol.*, *16*(4), 1502–1520.
- Collischonn, W., D. G. Allasia, B. C. Silva, and C. E. M. Tucci (2007), The MGB-IPH model for large-scale rainfall-runoff modeling, *Hydrol. Sci. J.*, *52*, 878–895.
- Cretaux, J. F., et al. (2011), SOLS: A lake database to monitor in the near real time water level and storage variations from remote sensing data, *Adv. Space Res.*, *47*, 1497–1507.
- Cunge, J. A., F. M. Holly, and A. Verney (1980), *Practical Aspects of Computational River Hydraulics*, Pitman Adv. Publ. Program, London.
- Da Silva, J. S., S. Calmant, F. Seyler, O. C. Rotunno Filho, G. Cochonneau, and W. J. Mansur (2011), Water levels in the Amazon basin derived from the ERS 2 and ENVISAT radar altimetry missions, *Remote Sens. Environ.*, *114*, 2160–2181.
- David, C. H., D. R. Maidment, G. Y. Niu, Z. L. Yang, F. Habets, and V. Eijkhout (2011), River network routing on the NHDPlus dataset, *J. Hydrometeorol.*, *12*(5), 913–934, doi:10.1175/2011JHM1345.1.
- de Almeida, G. A. M., P. D. Bates, M. Souvignat, and J. E. Freer (2012), Improving the stability of a simple formulation of the shallow water equations for 2D flood modelling, *Water Resour. Res.*, *48*, W05528, doi:10.1029/2011WR011570.
- Decharme, B., R. Alkama, F. Papa, S. Faroux, H. Douville, and C. Prigent (2012), Global off-line evaluation of the ISBA-TRIP flood model, *Clim. Dyn.*, *38*, 1389–1412, doi:10.1007/s00382-011-1054-9.
- Döll, P., K. Fiedler, and J. Zhang (2009), Global-scale analysis of river flow alterations due to water withdrawals and reservoirs, *Hydrol. Earth Syst. Sci.*, *13*, 2413–2432.
- Ek, M., K. Mitchell, L. Yin, P. Rogers, P. Grunmann, V. Koren, G. Gayno, and J. Tarpley (2003), Implementation of Noah landsurface model advances in the NCEP operational mesoscale eta model, *J. Geophys. Res.*, *108*(D22), 8851, doi:10.1029/2002JD003296.
- Fenton, J. D. (2001), Rating curves: Part 1—Correction for surface slope, in *Conference on Hydraulics in Civil Engineering*, pp. 309–317, The Inst. of Eng., Hobart, Tas., Australia.
- Getirana, A., A. McNally, J. Roningen, B. Zaitchik, K. Arsenault, H. C. Jung, and C. Peters-Lidard (2015), Forecasting water availability in data sparse and heavily managed catchments in Africa and the Middle East, *Gewex News*, *27*(4), 8–11.
- Getirana, A., A. Boone, and C. Peugeot (2017), Streamflows over a West African basin from the ALMIP-2 model ensemble, *J. Hydrometeorol.*, doi:10.1175/JHM-D-16-0233.1.
- Getirana, A. B., D. Yamazaki, B. Decharme, F. Papa, and N. Mognard (2012), The hydrological modeling and analysis platform (HyMAP): Evaluation in the Amazon basin, *J. Hydrometeorol.*, *13*, 1641–1665, doi:10.1175/JHM-D-12-021.1.
- Getirana, A. C. V., and R. C. D. Paiva (2013), Mapping large scale river flow hydraulics in the Amazon basin, *Water Resour. Res.*, *49*, 2437–2445, doi:10.1002/wrcr.20212.
- Getirana, A. C. V., A. Boone, D. Yamazaki, and N. Mognard (2013), Automatic parameterization of a flow routing scheme driven by radar altimetry data: Evaluation in the Amazon basin, *Water Resour. Res.*, *49*, 614–629, doi:10.1002/wrcr.20077.
- Getirana, A. C. V., A. Boone, and C. Peugeot (2014a), Evaluating LSM-based water budgets over a West African basin assisted with a river routing scheme, *J. Hydrometeorol.*, *15*, 2331–2346, doi:10.1175/JHM-D-14-0012.1.
- Getirana, A. C. V., et al. (2014b), Water balance in the Amazon basin from a land surface model ensemble, *J. Hydrometeorol.*, *15*, 2586–2614, doi:10.1175/JHM-D-14-0068.1.
- Getirana, A. C. V., S. Kumar, C. Peters-Lidard, and K. Arsenault (2014c), Water budget in the Amazon basin and impacts on flood modeling, *IAHS Publ.*, *363*, 407–412.
- Guimberteau, M., et al. (2012), Discharge simulation in the sub-basins of the Amazon using ORCHIDEE forced by new datasets, *Hydrol. Earth Syst. Sci.*, *16*, 911–935, doi:10.5194/hess-16-911-2012.
- Haddeland, I., D. P. Lettenmaier, and T. Skaugen (2006), Effects of irrigation on the water and energy balances of the Colorado and Mekong river basins, *J. Hydrol.*, *324*(1–4), 210–223.
- Hanasaki, N., S. Kanae, and T. Oki (2006), A reservoir operation scheme for global river routing models, *J. Hydrol.*, *327*, 22–41.
- Kirpich, Z. P. (1940), Time of concentration of small agricultural watersheds, *Civ. Eng.*, *10*, 362.
- Kumar, S. V., et al. (2006), Land information system: An interoperable framework for high resolution land surface modeling, *Environ. Modell. Software*, *21*, 1402–1415, doi:10.1016/j.envsoft.2005.07.004.
- Kumar, S. V., C. D. Peters-Lidard, K. Arsenault, A. C. V. Getirana, D. Mocko, and Y. Liu (2015), Quantifying the added value of snow cover area observations in passive microwave snow depth data assimilation, *J. Hydrometeorol.*, *16*, 1736–1741, doi:10.1175/JHM-D-15-0021.1.
- Kumar, S. V., et al. (2016), Assimilation of gridded GRACE terrestrial water storage estimates in the North American Land Data Assimilation System, *J. Hydrometeorol.*, *17*, 1951–1972, doi:10.1175/JHM-D-15-0157.1.
- Li, H., L. R. Leung, A. C. V. Getirana, M. Huang, H. Wu, Y. Xu, J. Guo, and N. Voisin (2015), Evaluating global streamflow simulations by a physically-based routing model coupled with the community land model, *J. Hydrometeorol.*, *16*, 948–971, doi:10.1175/JHM-D-14-0079.1.
- Lohmann, D., R. Nolte-Holube, and E. Raschke (1996), A large-scale horizontal routing model to be coupled to land surface parametrization schemes, *Tellus, Ser. A*, *48*(5), 708–721.
- Luo, X., H. Li, L. R. Leung, T. K. Tesfa, A. Getirana, F. Papa, and L. L. Hess (2017), Modeling surface water dynamics in the Amazon Basin using MOSART-Inundation-v1.0: Impacts of geomorphological parameters and river flow representation, *Geosci. Model Dev.*, *10*, 1233–1259, doi:10.5194/gmd-10-1233-2017.
- Masson, V., J.-L. Champeaux, C. Chauvin, C. Meriguet, and R. Lacaze (2003), A global database of land surface parameters at 1-km resolution in meteorological and climate models, *J. Clim.*, *16*, 1261–1282.
- Miller, J., G. Russell, and G. Caliri (1994), Continental scale river flow in climate models, *J. Clim.*, *7*, 914–928.
- Moussa, R., and C. Bocquillon (1996), Criteria for the choice of flood routing methods in natural channels, *J. Hydrol.*, *186*, 1–30.
- Oki, T., and Y. C. Sud (1998), Design of total runoff integrating pathways (TRIP)—A global river channel network, *Earth Interact.*, *2*, 1–36, doi:10.1175/1087-3562(1998)002,0001:DOTRIP.2.3.CO;2.
- Paiva, R. C. D., W. Collischonn, and D. C. Buarque (2013), Validation of a full hydrodynamic model for large-scale hydrologic modelling in the Amazon, *Hydrol. Processes*, *27*, 333–346, doi:10.1002/hyp.8425.
- Paz, A. R., W. Collischonn, C. E. M. Tucci, and C. R. Padovani (2011), Large-scale modelling of channel flow and floodplain inundation dynamics and its application to the Pantanal (Brazil), *Hydrol. Processes*, *25*, 1498–1516, doi:10.1002/hyp.7926.
- Reggiani, P., E. Todini, and D. Meißner (2014), Analytical solution of a kinematic wave approximation for channel routing, *Hydrol. Res.*, *45*(1), 43–57, doi:10.2166/nh.2013.157.

- Sheffield, J., G. Goteti, and E. F. Wood (2006), Development of a 50-year high-resolution global dataset of meteorological forcings for land surface modeling, *J. Clim.*, *19*, 3088–3111, doi:10.1175/JCLI3790.1.
- Vorosmarty, C. J., B. Moore III, A. L. Grace, and M. P. Gildea (1989), Continental scale models of water balance and fluvial transport: An application to South America, *Global Biogeochem. Cycles*, *3*, 241–265, doi:10.1029/GB003i003p00241.
- Yamazaki, D., S. Kanae, H. Kim, and T. Oki (2011), A physically based description of floodplain inundation dynamics in a global river routing model, *Water Resour. Res.*, *47*, W04501, doi:10.1029/2010WR009726.
- Yamazaki, D., G. A. M. de Almeida, and P. D. Bates (2013), Improving computational efficiency in global river models by implementing the local inertial flow equation and a vector-based river network map, *Water Resour. Res.*, *49*, 7221–7235, doi:10.1002/wrcr.20552.