Pianosi, F., & Wagener, T. (2018). Distribution-based sensitivity analysis from a generic input-output sample. *Environmental Modelling and Software*, 108, 197-207.
<https://doi.org/10.1016/j.envsoft.2018.07.019>

Peer reviewed version

License (if available):
CC BY-NC-ND

Link to published version (if available):
[10.1016/j.envsoft.2018.07.019](https://doi.org/10.1016/j.envsoft.2018.07.019)

[Link to publication record in Explore Bristol Research](#)
PDF-document

This is the author accepted manuscript (AAM). The final published version (version of record) is available online via Elsevier at <https://www.sciencedirect.com/science/article/pii/S1364815218303220> . Please refer to any applicable terms of use of the publisher.

University of Bristol - Explore Bristol Research

General rights

This document is made available in accordance with publisher policies. Please cite only the published version using the reference above. Full terms of use are available:
<http://www.bristol.ac.uk/red/research-policy/pure/user-guides/ebr-terms/>

Distribution-based sensitivity analysis from a generic input-output sample

Francesca Pianosi ^{a,b}, Thorsten Wagener ^{a,b}
(corresponding author: francesca.pianosi@bristol.ac.uk)

^a*Department of Civil Engineering, University of Bristol, University Walk,
BS81TR, Bristol, UK*

^b*Cabot Institute, University of Bristol, Royal Fort House, BS81UJ, Bristol, UK*

Abstract

In a previous paper we introduced a distribution-based method for Global Sensitivity Analysis (GSA), called PAWN, which uses cumulative distribution functions of model outputs to assess their sensitivity to the model's uncertain input factors. Over the last three years, PAWN has been employed in the environmental modelling field as a useful alternative or complement to more established variance-based methods. However, a major limitation of PAWN up to now was the need for a tailored sampling strategy to approximate the sensitivity indices. Furthermore, this strategy required three tuning parameters whose optimal choice was rather unclear. In this paper, we present an alternative approximation procedure that tackles both issues and makes PAWN applicable to a generic sample of inputs and outputs while requiring only one tuning parameter. The new implementation therefore allows the user to estimate PAWN indices as complementary metrics in multi-method GSA applications without additional computational cost.

Key words: global sensitivity analysis; distribution-based methods; moment-independent methods; multi-method GSA

1 Highlights

- 2 • We introduce a new approximation strategy for PAWN indices
- 3 • The strategy is applicable to a generic input-output sample and uses one
- 4 tuning parameter only
- 5 • We demonstrate that the strategy provides robust PAWN sensitivity es-
- 6 timates
- 7 • This approximation strategy facilitates the integration of PAWN into
- 8 multi-method GSA

9 Software availability

10 The PAWN algorithm, including the new approximation strategy presented
11 in this paper, are implemented in Matlab/Octave as part of the SAFE Tool-
12 box, which is freely available for non-commercial use through the website:
13 www.safetoolbox.info

14 1 Introduction

15 Global Sensitivity Analysis (GSA) is a set of techniques aimed at investigating
16 the propagation of uncertainty through mathematical models in a structured
17 way. More specifically, according to the widely used definition by Saltelli et al.
18 (2008), the aim of GSA is to quantify the relative contribution of the uncer-
19 tain input factors of a mathematical model to the variability of its outputs.
20 For model developers, such quantification can aid the process of identifying
21 a minimum complexity model by eliminating non-influential components. For
22 model users, it can make the calibration process more efficient by determining
23 the subset of model parameters whose reduction in uncertainty would mostly
24 reduce output variability, or it can be used to assess the robustness of the
25 model predictions against various sources of uncertainty such as errors in the
26 forcing data or even in uncertain modelling assumptions. GSA is therefore
27 widely applied in the environmental modelling field to support the construc-
28 tion, improvement and use of mathematical models (e.g. Beven and Binley
29 (1992); Spear et al. (1994); Freer et al. (1996); Bastidas et al. (1999); Wagener
30 and Kollat (2007); Norton (2015); Razavi and Gupta (2015); Xiaomeng et al.
31 (2015); Ferretti et al. (2016); Pianosi et al. (2016); Petropoulos and Srivastava
32 (2017)).

33 Many different GSA methods are available depending on the specific purposes
34 of the analysis as well as the characteristics of the mathematical model be-
35 ing analysed and its sources of uncertainty (Saltelli et al., 2008; Norton, 2015;
36 Pianosi et al., 2016). Among them, some of the most widely used are Variance-
37 Based Sensitivity Analysis (VBSA) methods, which measure output sensitiv-
38 ity as the proportion of output variance that is attributable to variations of
39 each uncertain input factor. For an overview of variance-based methods and
40 their advantages see for example Saltelli et al. (2008) or Pianosi et al. (2016).
41 Recently, density-based approaches have also gained increasing attention Cas-
42 taings et al. (2012); Anderson et al. (2014); Peeters et al. (2014); Dell’Oca
43 et al. (2017); Borgonovo et al. (2017). In these approaches, uncertainty and
44 sensitivity is characterised by investigating the entire distribution of the model
45 outputs, instead of its variance only. For this reason, such methods are also
46 referred to as *distribution-based* or *moment-independent*. Distribution-based

47 strategies are particularly suitable when variance is not an adequate proxy
48 of uncertainty, for example when the output distribution is highly-skewed or
49 multi-modal (e.g. Liu et al. (2006)).

50 In a previous paper (Pianosi and Wagener, 2015) we introduced a distribution-
51 based method, called PAWN, and implemented it as part of our open-source
52 GSA Toolbox called SAFE (Pianosi et al., 2015). The advantage of PAWN
53 over other moment-independent methods is that it characterises output dis-
54 tributions by their cumulative distribution functions, instead of their proba-
55 bility density functions, which makes the numerical approximation of PAWN
56 sensitivity indices easy and robust. In Pianosi and Wagener (2015) we demon-
57 strated the PAWN method by applying it to a standard benchmark function
58 and a simple rainfall-runoff model (Hymod). In Zadeh et al. (2017) we carried
59 out a systematic comparison between PAWN and variance-based method on
60 a medium complexity (26 parameters) hydrological model (SWAT) and found
61 that PAWN and VBSA had similar convergence rate and screening results,
62 while PAWN was more effective for parameter ranking as it could better sep-
63 arate out the relative importance of the influential parameters. Since its pub-
64 lication, PAWN has been used to investigate the role of uncertain parameters
65 across a range of environmental modelling fields, including: a transport model
66 of indoor air pollutant (Sedighian et al., 2015), a computational model of bio-
67 logical processes (Gillies et al., 2016), rainfall-runoff and land-surface models
68 in Pianosi and Wagener (2016) and Pianosi et al. (2017), a fluid flow and heat
69 transport model in geothermal reservoirs (Fox et al., 2016), a groundwater
70 model for karst systems (Hosseini et al., 2017), and a numerical algorithm for
71 hillslope-based landscape discretisation (Pilz et al., 2017).

72 Despite this relatively quick uptake of PAWN across different fields of applica-
73 tion, from our own experience and the feedbacks we received from other users,
74 we think two main issues remain critical. First, the numerical procedure we
75 proposed in our original paper to implement PAWN uses a *tailored* sampling
76 strategy, i.e. a strategy that selects input samples in specific regions of the
77 input variability space, according to the approximation procedure set out for
78 the PAWN indices. This is in contrast to *generic* sampling strategies, such as
79 sampling over a uniform grid, quasi-random sampling (Press et al., 1992) or
80 (stratified or not) random sampling, e.g. Latin Hypercube (Forrester et al.,
81 2008), which aim at spreading input samples as uniformly as possible across
82 the variability space, and can be used across a range of uncertainty and sensi-
83 tivity analysis methods. The requirement of a tailored sampling strategy thus
84 makes it more difficult to integrate PAWN into a multi-method GSA study,
85 such as Pappenberger et al. (2008) or Tang et al. (2007), since its inclusion
86 would require additional dedicated model evaluations. We believe that this
87 is a strong limitation given the value of applying multiple GSA methods to
88 the same problem as a way to validate and complement the results of indi-
89 vidual methods (Pianosi et al., 2015; Borgonovo et al., 2017). Additionally,

the requirement of a tailored sampling strategy prevents the application to an existing input-output dataset in cases where such a dataset is available from previous studies. These limitations have motivated researchers to seek for generic approximation strategies for other GSA methods too, including variance-based methods. For example, Strong et al. (2014) and Stanfill et al. (2015) have proposed new approximation strategies to derive first-order and total-order indices from a generic input-output dataset, as an alternative to the ‘traditional’ approximators (e.g. Saltelli et al. (2010)) based on ‘re-sample’ matrices, which require a tailored sampling strategy. A general discussion of the value of approximation procedures that can be applied to given data is given in Plischke et al. (2013).

The second issue with our tailored sampling strategy is that it requires users to specify three tuning parameters, i.e. the number of unconditional output samples (N_u), the number of conditional output samples (N_c), and the number of conditioning points (n). As discussed in Pianosi and Wagener (2015), the choice of these tuning parameters should be based on a compromise between approximation accuracy and computational burden, which both increase with any increase of N_u or N_c or n . In fact, the total number of model evaluations to approximate all PAWN indices is $N=N_u+n\times N_c\times M$, where M is the number of uncertain input factors. If each model evaluation is computationally demanding, either in terms of running time or data storage requirement, one would like to find the ‘optimal’ combination of (N_u, N_c, n) to reach sufficient approximation accuracy at minimum N . However, such optimal values are difficult to predict a priori and extrapolating from previous applications may be risky because the optimal values may change with the problem at hand, i.e. with the mathematical model, the number of input factors, and possibly even with the output definition or application domain (Sarrazin et al., 2016). We indeed know that the approximation accuracy associated with sensitivity indices at a given sample size can dramatically change with any element of the experimental set-up, as shown for example in Figure 5 in Pianosi et al. (2016) or Figures 2 and 3 in Zadeh et al. (2017).

In this paper we simultaneously address these two issues by introducing a new approximation procedure of the PAWN indices that (1) is applicable to a generic dataset; (2) requires fewer tuning parameters (essentially only the number of conditioning points n) whose choice is easier to make and to evaluate. The approximation procedure was already sketched out in the conclusions of Pianosi and Wagener (2015) and a similar idea was tested in Pianosi et al. (2017). Here we further develop those ideas into a new approximation procedure. We test it comprehensively on a benchmark function and on a complex hydrological model (the Soil Water Assessment Tool, in a set-up that includes 50 uncertain parameters). And finally, we propose a number of simple tools to assess the accuracy of the resulting PAWN indices as well as their robustness to the chosen tuning parameter, at negligible additional computing costs.

133 2 Methods

134 In this paper, we consider an input-output relationship

$$y = f(\mathbf{x}) \quad (1)$$

135 where $\mathbf{x} = [x_1, x_2, \dots, x_M] \in \mathcal{X} \subseteq \mathbb{R}^M$ is a vector of M input factors and
136 $y \in \mathbb{R}$ is a (scalar) output variable. The goal of GSA is to quantify the relative
137 contribution of variations in each input factor x_i to the variability of the
138 output y . A quantitative measure of such relative contribution is expressed by
139 the value of a sensitivity index S_i , typically ranging from 0 to 1.

140 The function f can be available either in closed form or as a numerical proce-
141 dure to compute y given $\mathbf{x}$. For example, in typical environmental modelling
142 applications the function f typically refers to the numerical procedure for
143 simulating a dynamical system over a given space-time domain. In this case,
144 the output y is a scalar variable that summarises the wide range of variables
145 (often time series, possibly spatially-distributed) provided by the simulation
146 procedure. For example y may be the value of a simulated variable at a time
147 and location of interest, or an aggregate measure of the mismatch between
148 some of the simulated variables and their observations, i.e. an objective or
149 loss function.

150 When the input-output relationship f is available in closed form (as in the
151 example of Sec. 4.1), it is often referred to as a *model*. When instead it refers
152 to the simulation procedure to compute y from $\mathbf{x}$ (as in Sec. 4.2), it is often
153 referred to as a *response surface*, to avoid confusion with the underlying set of
154 differential equations, which is also called a (simulation) model. Notice that in
155 the latter case, the underlying simulation model might have more inputs than
156 those included in $\mathbf{x}$ and the output y may be defined in different ways. The
157 choice of which variables to include in $\mathbf{x}$ and of how to define one (or multiple)
158 y depends on the underlying motivation for carrying out GSA, and as such it
159 is a subjective choice of the GSA user and will not be discussed here.

160 2.1 The PAWN method

161 The key idea of distribution-based methods is that the influence of an input
162 factor is proportional to the amount of change in the output distribution
163 produced by fixing that input. More precisely, the sensitivity of y to x_i is
164 measured by the difference between the unconditional distribution of y , which
165 is induced by varying all input factors simultaneously, and the conditional
166 distribution that is obtained by varying all inputs but x_i .

167 A review of several distribution-based methods is given in Pianosi and Wa-
 168 gener (2015). The distinctive feature of PAWN is that, in contrast to other
 169 methods, it uses (conditional and unconditional) cumulative distribution func-
 170 tions (CDFs) of the output instead of probability density functions. The ad-
 171 vantage of using CDFs is that their approximation from an output sample of
 172 finite size is easy and robust. Several other advantages of PAWN are discussed
 173 in Pianosi and Wagener (2015).

174 The PAWN sensitivity index for the i -th input factor is defined as

$$S_i = \text{stat} \max_{x_i} \max_y |F_y(y) - F_{y|x_i}(y|x_i)| \quad (2)$$

175 where $F_y(y)$ and $F_{y|x_i}(y|x_i)$ are the unconditional and conditional CDFs of the
 176 output y , and *stat* is a statistic (e.g. maximum, median or mean) defined by
 177 the user. Notice that the inner maximum in Eq. (2), i.e. the maximum abso-
 178 lute difference between CDFs, is no other than the Kolmogorov-Smirnov (KS)
 179 statistic, which is widely used as a measure of distance between CDFs (Kol-
 180 mogorov, 1933; Smirnov, 1939). The PAWN index can thus be reformulated
 181 as

$$S_i = \text{stat}_{x_i} \text{KS}(x_i) \quad \text{where} \quad \text{KS}(x_i) = \max_y |F_y(y) - F_{y|x_i}(y|x_i)| \quad (3)$$

182 Other statistics could possibly be used instead of KS. For example, Zadeh
 183 et al. (2017) tested the Anderson-Darling statistic and found that, in their
 184 application, it provides almost identical sensitivity results as the KS (these
 185 results are shown in their Supplementary material). Throughout this paper
 186 we will use KS, however our newly proposed approximation strategy could be
 187 equally applied to PAWN indices defined using other statistics.

188 2.2 Approximating PAWN indices using a tailored sampling strategy

189 In general, given the complexity of the input-output relationship f , the sensi-
 190 tivity indices of Eq. (2) cannot be computed analytically and they need to be
 191 approximated numerically. Pianosi and Wagener (2015) proposed an approx-
 192 imation procedure based on two simplifications. First, using a finite number
 193 of conditioning points $\bar{x}_i^{(1)}, \bar{x}_i^{(2)}, \dots, \bar{x}_i^{(n)}$ for each input factor, instead of all its
 194 possible values. Second, replacing the distributions F_y and $F_{y|x_i}$ by the em-
 195 pirical distributions $\hat{F}_y$ and $\hat{F}_{y|x_i}$ of output samples of finite size. Specifically,
 196 $\hat{F}_y$ is the empirical distribution of an unconditional sample (YU) obtained by
 197 varying all input factors simultaneously, and $\hat{F}_{y|x_i}$ is the empirical distribution
 198 of a conditional sample (YC _{i k}) obtained by varying all factors but the i -th,
 199 which is set to the k -th conditioning value $\bar{x}_i^{(k)}$. The PAWN sensitivity index

200 is then approximated by

$$\hat{S}_i = \text{stat}_{k=1,\dots,n} \text{KS}(\bar{x}_i^{(k)}) \text{ where } \text{KS}(\bar{x}_i^{(k)}) = \max_y |\hat{F}_y(y) - \hat{F}_{y|x_i}(y|x_i = \bar{x}_i^{(k)})| \quad (4)$$

201 The left hand side of Figure 1 provides a visual illustration of this approx-
 202 imation strategy for the simple case of $M=3$ input factors. For the sake of
 203 illustration, the Figure focuses on approximating the PAWN sensitivity index
 204 of the first input factor (x_1). The top left panels (Fig. 1(a) and (b)) show the
 205 combinations of input factors (x_1, x_2, x_3) that need to be evaluated in order to
 206 obtain the unconditional sample and three conditional samples correspond-
 207 ing to $n=3$ fixed values of x_1 . The corresponding output samples (YU, YC₁₁,
 208 YC₁₂, YC₁₃) are visualised via a scatter plot in Fig. 1(c). The lower panels
 209 show the further steps for computing the approximate PAWN index $\hat{S}_1$: com-
 210 puting the empirical distributions of YU (red line in (g)) and of YC₁₁, YC₁₂
 211 and YC₁₃ (grey lines), computing the KS at each conditioning point (h), and
 212 finally taking a statistic, e.g. the median, of those KS values. A similar pro-
 213 cedure would be applied for approximating the sensitivity indices of x_2 and
 214 x_3 .

215 We call the approach underpinning Eq. (4) a *tailored sampling strategy* because
 216 a large part of the input samples generated to compute the sensitivity indices,
 217 namely all those in the conditional samples YC_{ik} for $k = 1, \dots, n$, are concen-
 218 trated in specific subregions of the input variability space (e.g. the planes in
 219 Fig.1(b) where the grey circles lie). This is in contrast to *generic sampling*
 220 *strategies* that would spread input samples as evenly as possible across the
 221 input space (e.g. the samples in Fig. 1(d)-(e)). Examples of generic sampling
 222 strategies include latin hypercube sampling (e.g. Sec. 1.4 in Forrester et al.
 223 (2008)) or quasi-random sampling (e.g. Sec. 7.7 in Press et al. (1992)). Notice
 224 that while the input samples in YC_{ik} may be generated by applying a generic
 225 sampling strategy in the $(M - 1)$ -dimensional space of all-inputs-but-the- i -th
 226 (for instance, we will use latin hypercube sampling in the following case study
 227 applications), collectively the ensemble of conditional samples YC_{ik} does not
 228 constitute a *generic* dataset in the M -dimensional input variability space, as
 229 clearly shown in Fig. 1(b).

230 With the tailored sampling strategy, the total number of model evaluations
 231 to approximate all PAWN sensitivity indices is $N_u + n \times N_c \times M$, where N_u is
 232 the size of the unconditional sample YU, N_c is the size of each conditional
 233 sample YC_{ik}, and M is the number of input factors (and hence sensitivity in-
 234 dices). As discussed in the Introduction, the issue of how to choose the triple
 235 (N_u, n, N_c) has not been formally investigated and it remains an open question
 236 in the application of PAWN. This choice is critical given that it affects both
 237 the accuracy of the PAWN indices and the computational effort (total num-
 238 ber of model evaluations) to generate them. Another issue with the tailored
 239 strategy is that much of the computational effort is invested in generating

the conditional samples YC_{ik} , which cannot be re-used in other uncertainty or sensitivity analysis methods that would require a generic sample. To overcome these two issues we present a novel approach to approximate PAWN indices from a generic dataset in the next section.

2.3 Approximating PAWN indices from a generic dataset

So how can we approximate the sensitivity index in Eq. (2) using a generic input-output dataset $\langle X, Y \rangle$, for example a dataset generated by Latin hypercube sampling? A possible way to do this is to split the range of variation of each input factor x_i into n equally spaced intervals $\mathcal{I}_k$ and define the conditional samples YC_{ik} accordingly. The unconditional sample YU could instead coincide with the entire sample Y or with a subsample of it. Such a strategy corresponds to approximate PAWN sensitivity indices as:

$$\hat{S}_i = \text{stat}_{k=1, \dots, n} \text{KS}(\mathcal{I}_k) \quad \text{where} \quad \text{KS}(\mathcal{I}_k) = \max_y |\hat{F}_y(y) - \hat{F}_{y|x_i}(y|x_i \in \mathcal{I}_k)| \quad (5)$$

A visual illustration of the splitting strategy for creating unconditional and conditional samples from a generic dataset is given on the right hand side of Figure 1 ((d) and (e)). Once the output samples have been built (Fig 1(f)), the subsequent steps for approximating PAWN sensitivity indices are the same than when the tailored sampling strategy is used. A summary comparison of the workflows underpinning Eq. (4) and (5) is given in Figure 2.

When using the approximation strategy of Eq. (5), the size of the conditional sample (N_c) does not need to be specified by the user: it simply coincides with the number of points in each interval $\mathcal{I}_k$. However, if input samples are uniformly spread in the given dataset we may expect N_c to be approximately equal to N/n , where N is the size of the generic dataset. Therefore, the user can indirectly control the value of N_c by choosing n : a reduction in n would increase N_c and vice versa. As for the unconditional sample, one option is to let it coincide with the sample Y . This choice would correspond to setting $N_u = N$. Another option is to use a subsample of Y , for example by randomly extracting a subsample of the same size as the conditional ones (i.e. setting $N_u = N_c$). The latter option has the advantage that the compared unconditional and conditional distributions are estimated from the same number of samples. Furthermore, the random extraction from Y can be repeated several times using bootstrapping without replacement as a way to test the robustness of the PAWN sensitivity indices, as will be further described in the next subsection.

In either case, the main point here is that both N_c and N_u do not need to be chosen by the user but they are determined as a consequence of the chosen value of n and N . This is an advantage with respect to the tailored sampling

276 approach because the number of tuning parameters is reduced to two (instead
 277 of three) but most importantly because selecting their values is much easier. In
 278 fact, when using a generic dataset the computational effort for approximating
 279 the PAWN sensitivity indices is fully controlled by the chosen value for N .
 280 Hence, an obvious choice is to take the largest value possible for N given
 281 available computing resources. As for n , it only has an effect on the splitting
 282 of the input-output dataset $\langle X, Y \rangle$ but not on its generation. Consequently,
 283 one can attempt different values of n and evaluate the robustness of GSA
 284 results to this choice without significantly adding to the overall computational
 285 effort. Further ways to assess the robustness of PAWN sensitivity indices to
 286 the chosen sample size N are discussed in the next subsection and will be
 287 illustrated in the Results section.

288 2.4 Estimating the robustness of PAWN indices

289 When sensitivity indices are computed by an approximate formula such as Eq.
 290 (4) or (5), it is very important to evaluate the robustness of the sensitivity
 291 values to the chosen sample, particularly if the sample size is small. A compu-
 292 tationally efficient way to do this is by repeating sensitivity calculations using
 293 different bootstrap resamples (Efron and Tibshirani, 1993) of the available
 294 input-output dataset to obtain a distribution of sensitivity indices. The mean
 295 of such distributions can be taken as a more robust estimate of the sensitiv-
 296 ity indices (at least more robust than the point estimates obtained without
 297 bootstrapping) and quantiles can be computed to derive confidence intervals
 298 around those estimates (Yang, 2011; Sarrazin et al., 2016).

299 Additionally, the impact of approximation errors on sensitivity indices can be
 300 directly inferred by using a so called *dummy parameter* (Zadeh et al., 2017).
 301 A dummy parameter is an input factor that is artificially introduced in the
 302 analysis and that, by definition, cannot affect the output variability. However,
 303 the sensitivity index of the dummy parameter may still be larger than zero,
 304 because of errors in the employed approximation procedure. The value of the
 305 dummy sensitivity index thus provides an indication of the extent of approxi-
 306 mation errors and can be used to put all other sensitivity results into context.
 307 In fact, if an input factor is associated with a sensitivity index significantly
 308 larger than the dummy sensitivity, then one can sensibly conclude that this
 309 input factor is indeed influential. If instead the approximate sensitivity index
 310 is equal or even smaller than the dummy sensitivity, then nothing can be con-
 311 cluded about this input factor because its non-zero sensitivity may be due
 312 to an actual effect of the input on the output or be purely a consequence of
 313 approximation errors.

314 In the case of PAWN sensitivity indices, a dummy parameter should in prin-

315 ciple have zero sensitivity because if a parameter has no effect on the out-
 316 put, then fixing its value has no effect on the output distribution, hence
 317 $F_y = F_{y|x_{\text{dummy}}}$ at all conditioning values of x_{dummy} in Eq. (2) and $S_{\text{dummy}} = 0$.
 318 However, the dummy parameter might have a positive approximate sensitivity
 319 index ($\hat{S}_{\text{dummy}} > 0$) when using Eq. (4) or (5) because the empirical distri-
 320 butions $\hat{F}_y$ of two samples can differ from each other even if the samples are
 321 drawn from the same distribution F_y . The approximate sensitivity $\hat{S}_{\text{dummy}}$ can
 322 thus be interpreted as a measure of the accuracy in approximating CDFs by
 323 empirical distributions and hence of the accuracy of the estimated PAWN
 324 indices given the chosen sample size (Zadeh et al., 2017).

325 In this paper, we will use a very simple and straightforward approach to imple-
 326 ment these ideas. As suggested in the previous subsection, we will derive the
 327 unconditional sample YU by randomly extracting from Y a subsample of size
 328 N_c , and repeat the subsampling for a prescribed number of times. Given that
 329 by construction $N_c < N$, we can bootstrap *without replacement* (Efron and
 330 Tibshirani, 1993) from YU (the reasons for preferring resampling without re-
 331 placement when applying PAWN is discussed in the Supplementary Materials
 332 of Zadeh et al. (2017)). We will then apply Eq. (5) for each bootstrap resample
 333 of YU to derive a distribution of approximate PAWN sensitivity indices, and
 334 hence confidence intervals. Finally, we will estimate the PAWN sensitivity of
 335 the dummy parameter as:

$$\hat{S}_{\text{dummy}} = \text{mean} \max_{k=1, \dots, n} |\hat{F}_y^{(k)}(y) - \hat{F}_y^{(n+1)}(y)| \quad (6)$$

336 where $\hat{F}_y^{(k)}$ is the empirical distribution of the k -th bootstrap resample of the
 337 unconditional output sample YU.

338 3 Results

339 In this section we demonstrate the proposed approximation strategy from a
 340 generic dataset using two case studies. The former is a standard benchmark
 341 function widely used in the GSA literature and also used in Pianosi and Wa-
 342 gener (2015) to demonstrate PAWN with a tailored sampling strategy. The ob-
 343 jective of this application is to show whether the two approximation strategies
 344 provide similar results and to assess the impact of the tuning parameter n on
 345 a simple case study. Then, we apply our new strategy to a much more complex
 346 and more realistic case study, the Soil Water Assessment Tool (SWAT) model,
 347 in a set-up comprising 50 parameters. The objective of the latter application
 348 is to evaluate the scalability of the proposed PAWN approximation strategy
 349 to problems with many uncertain input factors. We also explore the impact of
 350 sample size on the sensitivity estimates, on input ranking and screening, and

to illustrate a simple approach to evaluate the effects of the tuning parameter n on PAWN sensitivity indices.

3.1 Application to Ishigami-Homma function

We first consider the Ishigami-Homma function

$$y = \sin(x_1) + a \sin(x_2)^2 + b x_3^4 \sin(x_1) \quad (7)$$

where $x_i \sim \mathcal{U}[-\pi, +\pi]$ for $i=1,2,3$ and $a=2$ and $b=1$. This function is often used in GSA studies because the variance-based sensitivities of y can be calculated analytically (see for instance Chapter 4 in Saltelli et al. (2008)), which makes it an ideal testing ground of approximate sensitivity estimators. In particular, the first-order (S_i^F) and total-order (S_i^T) variance-based sensitivity indices are $S_1^F=0.3830$, $S_1^T=0.9991$, $S_2^F=S_2^T=0.0009$, $S_3^F=0$, $S_3^T=0.6161$. According to these indices, x_1 is by far the most influential input, x_2 has very limited influence and no interactions, x_3 is only influential through interactions with x_1 .

The Ishigami-Homma function was used in Pianosi and Wagener (2015) as a testing ground for PAWN. In that work, the tailored sampling strategy was used and the KS values were aggregated across conditioning points by taking their median, i.e. $\text{stat}=\text{median}$ in Eq. (4). With these choices, PAWN sensitivity indices were found to be equal to $\hat{S}_1=0.48$, $\hat{S}_2=0.14$, $\hat{S}_3=0.30$, which provides input rankings of (x_1 as most influential, then x_3 , and finally x_2) consistent with the results of a variance-based analysis.

Here we re-compute the PAWN sensitivity indices using the proposed approximation strategy from a generic sample, i.e. according to Eq. (5) instead of Eq. (4). As a generic sampling strategy we use Latin Hypercube and we start by setting the tuning parameters to $N=500$ samples and $n=10$ conditioning intervals for each input factor. We repeat the calculations by bootstrapping without replacement, as described in Sec. 3.4. With this set-up, PAWN indices (median KS) are found equal to $\hat{S}_1=0.50$, $\hat{S}_2=0.16$, $\hat{S}_3=0.29$ (averages over 50 bootstrap resamples). These numbers are very consistent with those obtained using the tailored sampling strategy, which means that the two approximation approaches are essentially equivalent in this case. It is worth noticing that here we used a generic dataset of $N=500$ model evaluations, while in Pianosi and Wagener (2015) we used $N_u+n \times N_c \times M=100+15 \times 50 \times 3=2350$ model evaluations (although in Pianosi and Wagener (2015) we did not explore whether using less samples would have produced different results).

We further explore the impact of the sample size (N) and of the chosen number of conditioning intervals (n) in Figure 3. Each panel refers to a different

input factor, and it shows the median KS (again, average over 50 bootstrap resamples) for different choices of n (horizontal axis) and for different sample size (color). For each combination (N, n) , the Figure also shows the estimated PAWN sensitivity of the dummy parameter, computed by Eq. (6) (dashed line). The Figure shows that:

- As the sample size (N) increases, both the bootstrap confidence intervals and the value of $\hat{S}_{\text{dummy}}$ reduce. Furthermore, the median KS values stabilise, at least for larger n values (more on the impact of n in the next point). These patterns are expected and simply prove that the approximation strategy behaves sensibly. The more interesting fact is that using $N = 500$ samples provides very similar results as using $N=2000$, which means that the proposed approximation strategy provides robust results already at relatively small sample size in this particular case.
- The choice of n seems to have a limited effect on the sensitivity estimates as long as its value is sufficiently high (above 5 in our case). In fact, KS medians are essentially stable for any choice of $n > 5$ and close to the (presumed) correct values (we are now focusing on results for $N=500$ and $N=2000$, those obtained with $N=100$ being too imprecise). Notice that Figure 3 also reports results for $n=1$, i.e. the limit case where input-output samples are not split into intervals and hence, by definition, the PAWN sensitivity index is equal to 0. This set-up would never be used in practice, however it is shown here to prove that the method behaves consistent with expectations. Finally, sensitivity indices that are lower in values, i.e. those of inputs x_2 and x_3 , are more unstable at low values of n while the higher sensitivity index (that of x_1) is almost insensitive to the tuning parameter, which is again quite consistent with expectations. Basically, we see an effect of n only when (a) we use a very small sample size ($N=100$) and relatively large n so that the number of samples used for estimating output distributions becomes quite low (for example, for $n = 14$ we get $N_c=100/14 \sim 7$); (b) we use a very small value of n , for example 3 or 4, and then the sensitivity indices of less influential inputs (x_2 and x_3) are badly estimated.

To conclude, application of the proposed approximation strategy to a synthetic test function delivers reliable estimates of PAWN sensitivity indices (median KS) at relatively low sample size ($N \geq 500$) and quite irrespectively of the chosen value of the tuning parameter n (provided that $n > 5$).

3.2 Application to the SWAT model

The Soil and Water Assessment Tool (SWAT) is a semi-distributed hydrological model developed by the USDA Agricultural Research Service (Arnold

et al., 1998) and used worldwide to study the impact of land use and management practices on water quantity and quality at the catchment scale (e.g. Gassman et al. (2007)). Here, we use a model set-up for the upper Senne River basin in Belgium, which is described in Leta et al. (2015) and was used in a previous GSA study by Sarrazin et al. (2016) and comprises 50 uncertain parameters. The model output y considered in the GSA is a performance metric, the Nash-Sutcliffe efficiency (Nash and Sutcliffe, 1970), measuring the distance between daily flow predictions of the model and available observations. More information about the model, the application river basin and the definition of inputs and output for GSA can be found in Sarrazin et al. (2016). A list of the 50 model parameters and their variability ranges is given in the Supplementary Material of this paper. Here we re-use the input-output dataset generated for the Regional Sensitivity Analysis in Sarrazin et al. (2016), obtained by Latin Hypercube sampling and including $N = 10,000$ samples.

First, we approximate the PAWN sensitivity indices by Eq. (5) using $n=10$ conditioning intervals. We repeat our calculations with 100 bootstrap resamples and compute the averages and confidence intervals of each index, shown in Figure 4. According to this figure, the most influential parameter is the 11th, followed by parameters 9,32,10. Given that the confidence intervals for these three parameters are mostly overlapping, we cannot make further distinctions between them and thus we would put all of them in the 2nd position of the parameter ranking. Following the same line of reasoning, we would put parameters 8,17,2,43 in the 3rd position and parameters 14,25,42,34,12,28,35 in the 4th. The remaining parameters have an average sensitivity value close to that of the dummy parameter (red line in Figure 4), which means we cannot distinguish whether they actually have an influence on the output or whether their estimated sensitivity is a pure product of approximation errors. Hence, we classify them as potentially uninfluential. These ranking results are consistent with those obtained by Sarrazin et al. (2016) using other GSA methods. Figure 5 provides a short comparison with those results, focusing in particular on the top positions of the parameter ranking. The fact that only a limited number of parameters (4 to 8 in our case) control the output performance metric (Nash-Sutcliffe efficiency) is consistent with several studies on calibration of hydrological models (e.g. Jakeman and Hornberger (1993) and Van Werkhoven et al. (2009)). Furthermore, from the parameter list in the Supplementary Material, one can see that the 4 top-ranking parameters are: the SCS runoff curve number for moisture condition in the agricultural areas (11), the hydraulic conductivity in the river channel (9), the average slope steepness in the agricultural areas (32), and the Manning coefficient for the channel (10). This is reasonable given the predominance of agricultural land use in the catchment (62% of the catchment area as reported in Leta et al. (2015)) and the fact that the chosen output metric (Nash-Sutcliffe efficiency) emphasises errors in peak flow predictions, which we expect to be mainly controlled by the parameters that characterise river routing (see for

470 example Van Werkhoven et al. (2008)).

471 Next, we analyse the impact of the sample size N . To do this, we randomly
472 extract a subsample of smaller size from our original dataset and repeat the
473 approximation procedure of the PAWN sensitivity indices. We test $N=1000$,
474 5000 and 7500 (Figure 6). We find that using $N=1000$ (top panel) produces
475 rather imprecise sensitivity indices, in fact almost all confidence intervals over-
476 lap each other and with the dummy parameter threshold, which prevents us
477 from inferring a robust parameter ranking. However, already at the next sam-
478 ple size ($N=5000$) the confidence intervals start to separate out and the rank-
479 ing of the influential parameters is similar to the one obtained at the highest
480 sample size ($N=10000$).

481 The effect of the tuning parameter n is then analysed in Figure 7. The Figure
482 depicts the approximate PAWN sensitivity indices obtained using different
483 values of n from 6 to 20. Overall, the changes in value with varying n seem to be
484 minor. We observe a trend of increasing sensitivity values as n increases, i.e. the
485 grey shading gets darker from left to right. However this trend mainly involves
486 parameters with very low sensitivity and does not affect the key conclusion
487 that these parameters are probably uninfluential, as their approximate index
488 remains below that of the dummy parameter (cases flagged by red crosses).

489 Finally, we investigate the effect of the aggregation statistic. This is shown
490 in Figure 8 and 9, which are the analogues of Figure 6 using $\text{stat}=\text{mean}$ and
491 $\text{stat}=\text{max}$ in Eq. (5) instead of the median. Figure 8 shows that using the mean
492 KS provides very similar ranking and screening results as using the median.
493 Figure 9 instead reveals that using the max KS significantly increases the
494 relative importance of some input factors (e.g. parameters 43, 35 and 46). We
495 further investigate this behaviour in Figure 10, which shows the scatter plots
496 of the output samples for parameters 43, 35 and 46 (top panels) and the KS
497 values for different conditioning intervals (bottom panels). We also include the
498 results for the most influential input 11, as a reference. This figure shows that
499 the output is rather insensitive to variations in parameters 43, 35 and 46 for
500 most of their variability ranges with the exception of the very low end, where
501 the KS value is above the dummy parameter threshold. Further analysis (not
502 shown) reveals that in those sub-range the conditional output distributions
503 are shifted to the left of the unconditional ones i.e. lower output values are
504 more frequent. While further investigating the implications of this localised
505 effect is beyond the scope of this paper, we have shown this analysis as an
506 example of how PAWN can also be used to gain insights into the input-output
507 mapping, and reinforce the visual inspection of scatter plots with quantitative
508 evidence of local effects.

509 4 Conclusions

510 In this paper we have introduced and discussed a new strategy to approxi-
 511 mate PAWN sensitivity indices from a generic sample of model inputs and
 512 outputs using only one algorithm tuning parameter (the number n of condi-
 513 tioning intervals). Via application to a benchmark function (with 3 uncertain
 514 inputs) and to a complex hydrological model (50 uncertain parameters) we
 515 have demonstrated that the new approximation strategy provides results con-
 516 sistent with those of the original approximation strategy and of other GSA
 517 methods. Furthermore, the screening and ranking of uncertain inputs based
 518 on the new approximation strategy is reliable at reasonably low sample sizes
 519 (around $N=500$ samples in the 3 inputs case and 5000 in the 50 inputs case)
 520 and is robust against the choice of n . Obviously we cannot extrapolate from
 521 two case studies that these conclusions will hold true for any other application,
 522 however in this paper we have also provided a number of visualisation tools,
 523 such as those shown in Figure 3, 6 and 7, that can be used to evaluate the
 524 impact of N and n in any given application, at no additional computing cost.
 525 While we have followed a heuristic approach to the convergence of sensitivity
 526 estimates, the same issue is approached from a theoretical perspective in Bor-
 527 gonovo et al. (2016), who investigated the properties of a *partition selection*
 528 *strategy* (the splitting strategy, in our terminology) that ensure converge to
 529 true sensitivity values for the case when the aggregation statistic of KS values
 530 is the mean. Expanding those theoretical results to other aggregation statistics
 531 may be an interesting avenue for future research.

532 Based on the analyses presented in this paper, we can give the following prac-
 533 tical recommendations to future PAWN users:

- 534 • Always use the new approximation strategy instead of the tailored strat-
 535 egy presented in Pianosi and Wagener (2015). The functions to implement
 536 the new approximation strategy are now included in our open-source
 537 SAFE Toolbox (Pianosi et al., 2015).
- 538 • If a generic input-output dataset is available, you can re-use it to apply
 539 PAWN, otherwise generate one of size N as large as possible, compatibly
 540 with available computing resources. In both cases, compute the PAWN
 541 indices using both the complete dataset and subsets of smaller sizes, as
 542 done for example in Figure 6, to verify that the key conclusions about the
 543 ranking and screening of the input factors are not significantly affected
 544 by the value of N . If instead they are, the sample size should probably
 545 be increased.
- 546 • Use $n=10$ to start with but check the effects of varying n of some units
 547 up and down, as done in Figure 7.
- 548 • In all the analyses, use bootstrapping to derive confidence intervals and
 549 thus infer whether differences in sensitivity indices are large enough to

550 discriminate between the relevant inputs, or they should be put in the
551 same ranking position. Use the KS of the dummy parameter to identify
552 inputs whose measured sensitivity is too low to be distinguishable from
553 approximation errors.

554 Once again we stress that all these analyses (i.e. reducing N , changing n ,
555 bootstrapping, and calculation of the dummy KS) can be performed over the
556 available dataset and do not require to re-run the model, hence they come at
557 almost no additional computing cost. We hope this increased efficiency and
558 simplicity of the new approximation strategy will contribute to increase the
559 uptake of the PAWN method and facilitate its use as a complement of variance-
560 based sensitivity analysis and its integration into multi-method approaches to
561 GSA in general.

562 Acknowledgements

The initial development of the PAWN method and of the SAFE Toolbox was supported by the Natural Environment Research Council [Consortium on Risk in the Environment: Diagnostics, Integration, Benchmarking, Learning and Elicitation (CREDIBLE); grant number NE/J017450/1]. F Pianosi is partially funded by a UK EPSRC Living with Environmental Uncertainty Fellowship [grant number EP/R007330/1]. T Wagener is partially supported by a Royal Society Wolfson Research Merit Award. The authors are grateful to the researchers who used PAWN so far and, through their feedbacks and comments, motivated and gave directions for this study.

563 References

- 564 Anderson, B., Borgonovo, E., Galeotti, M., Roson, R., 2014. Uncertainty in
565 climate change modeling: can global sensitivity analysis be of help? Risk
566 Analysis 34 (2), 271 – 293.
- 567 Arnold, J., Srinivasan, R., Muttiah, R., Williams, J., 1998. Large area hydro-
568 logic modeling and assessment part 1: model development. J. Am. Water
569 Resour Assoc 34 (1), 73–89.
- 570 Bastidas, L. A., Gupta, H. V., Sorooshian, S., Shuttleworth, W. J., Yang,
571 Z. L., 1999. Sensitivity analysis of a land surface scheme using multicriteria
572 methods. Journal of Geophysical Research: Atmospheres 104 (D16), 19481–
573 19490.
- 574 Beven, K., Binley, A., 1992. The future of distributed models: Model calibra-
575 tion and uncertainty prediction. Hydrological Processes 6 (3), 279–298.

576 Borgonovo, E., Hazen, G., Plischke, E., 2016. A common rationale for global
577 sensitivity measures and their estimation. *Risk Analysis* 36, 1871–1895.

578 Borgonovo, E., Lu, X., Plischke, E., Rakovec, O., Hill, M. C., 2017. Making
579 the most out of a hydrological model data set: Sensitivity analyses to open
580 the model black-box. *Water Resources Research* 53, 7933–7950.

581 Castaings, W., Borgonovo, E., Morris, M., Tarantola, S., 2012. Sampling
582 strategies in density-based sensitivity analysis. *Environmental Modelling
583 & Software* 38 (0), 13–26.

584 Dell’Oca, A., Riva, M., Guadagnini, A., 2017. Moment-based metrics for global
585 sensitivity analysis of hydrological systems. *Hydrology and Earth System
586 Sciences* 21 (12), 6219–6234.

587 Efron, B., Tibshirani, R., 1993. *An Introduction to the Bootstrap*. Chapman
588 & Hall/CRC.

589 Ferretti, F., Saltelli, A., Tarantola, S., 2016. Trends in sensitivity analysis
590 practice in the last decade. *Science of The Total Environment* 568, 666–
591 670.

592 Forrester, A., Sobester, A., Keane, A., 2008. *Engineering Design via Surrogate
593 Modelling: a Practical Guide*. Wiley.

594 Fox, D., Koch, D., Tester, J., 2016. An analytical thermohydraulic model for
595 discretely fractured geothermal reservoirs. *Water Resources Research* 52 (9),
596 6792–6817.

597 Freer, J., Benev, K., Ambroise, B., 1996. Bayesian estimation of uncertainty
598 in runoff prediction and the value of data: An application of the GLUE
599 approach. *Water Resources Research* 32 (7), 2161–2173.

600 Gassman, P., Reyes, M. R., Green, C. H., Arnold, J. G., 2007. The Soil and
601 Water Assessment Tool: Historical development, applications, and future
602 research directions. *Transactions of the ASABE* 50 (4), 1211–1250.

603 Gillies, K., Krone, S., Nagler, J., Schultz, R., 2016. A computational model
604 of the rainbow trout hypothalamus-pituitary-ovary-liver axis. *PLOS com-
605 putational biology* 12 (4).

606 Hosseini, S., Ataie-Ashtiani, B., Simmons, C., 2017. Spring hydrograph sim-
607 ulation of karstic aquifers: Impacts of variable recharge area, intermediate
608 storage and memory effects. *Journal of Hydrology* 552, 225–240.

609 Jakeman, A., Hornberger, G., 1993. How much complexity is warranted in a
610 rainfall-runoff model? *Water Resources Research* 29, 2637–2649.

611 Kolmogorov, A., 1933. Sulla determinazione empirica di una legge di dis-
612 tribuzione. *Giornale dell’Istituto Italiano degli Attuari* 4, 83–91.

613 Leta, O., Nossent, J., Velez, C., Shrestha, N., van Griensven, A., Bauwens,
614 W., 2015. Assessment of the different sources of uncertainty in a SWAT
615 model of the river senne (belgium). *Environmental Modelling & Software*
616 68, 129–146.

617 Liu, H., Sudjianto, A., Chen, W., 2006. Relative entropy based method for
618 probabilistic sensitivity analysis in engineering design. *Journal of Mechan-
619 ical Design* 128, 326–336.

620 Nash, J., Sutcliffe, J., 1970. River flow forecasting through conceptual models,

621 Part I - A discussion of principles. *Journal of Hydrology* 10, 282–290.

622 Norton, J., 2015. An introduction to sensitivity assessment of simulation mod-
623 els. *Environmental Modelling & Software* 69, 166–174.

624 Pappenberger, F., Beven, K., Ratto, M., Matgen, P., 2008. Multi-method
625 global sensitivity analysis of flood inundation models. *Advances in Water*
626 *Resources* 31 (1), 1–14.

627 Peeters, L. J. M., Podger, G. M., Smith, T., Pickett, T., Bark, R. H., Cuddy,
628 S. M., 2014. Robust global sensitivity analysis of a river management model
629 to assess nonlinear and interaction effects. *Hydrology and Earth System*
630 *Sciences* 18 (9), 3777–3785.

631 Petropoulos, G., Srivastava, P., 2017. *Sensitivity Analysis in Earth Observa-*
632 *tion Modelling*. Elsevier.

633 Pianosi, F., Beven, K., Freer, J., Hall, J. W., Rougier, J., Stephenson, D. B.,
634 Wagener, T., 2016. Sensitivity analysis of environmental models: A system-
635 atic review with practical workflow. *Environmental Modelling & Software*
636 79, 214 – 232.

637 Pianosi, F., Iwema, J., Rosolem, R., Wagener, T., 2017. A Multimethod Global
638 Sensitivity Analysis Approach to Support the Calibration and Evaluation
639 of Land Surface Models. Amsterdam:Elsevier, pp. 125–144.

640 Pianosi, F., Sarrazin, F., Wagener, T., 2015. A matlab toolbox for global
641 sensitivity analysis. *Environmental Modelling & Software* 70, 80 – 85.

642 Pianosi, F., Wagener, T., 2015. A simple and efficient method for global sen-
643 sitivity analysis based on cumulative distribution functions. *Environmental*
644 *Modelling & Software* 67, 1 – 11.

645 Pianosi, F., Wagener, T., 2016. Understanding the time-varying importance
646 of different uncertainty sources in hydrological modelling using global sen-
647 sitivity analysis. *Hydrological Processes* 30 (22), 3991–4003.

648 Pilz, T., Francke, T., Bronstert, A., 2017. lumpR 2.0.0: an R package fa-
649 cilitating landscape discretisation for hillslope-based hydrological models.
650 *Geoscientific Model Development* 10 (8), 3001–3023.

651 Plischke, E., Borgonovo, E., Smith, C. L., 2013. Global sensitivity measures
652 from given data. *European Journal of Operational Research* 226 (3), 536 –
653 550.

654 Press, W., Teukolsky, S., Vetterling, W., Flannery, B., 1992. *Numerical Recipes*
655 *in C*. Cambridge University Press.

656 Razavi, S., Gupta, H., 2015. What do we mean by sensitivity analysis? the
657 need for comprehensive characterization of global sensitivity in earth and
658 environmental systems models. *Water Resources Research* 51 (5), 3070–
659 3092.

660 Saltelli, A., Annoni, P., Azzini, I., Campolongo, F., Ratto, M., Tarantola,
661 S., 2010. Variance based sensitivity analysis of model output. Design and
662 estimator for the total sensitivity index. *Computer Physics Communications*
663 181 (2), 259–270.

664 Saltelli, A., Ratto, M., Andres, T., Campolongo, F., Cariboni, J., Gatelli, D.,
665 Saisana, M., Tarantola, S., 2008. *Global Sensitivity Analysis, The Primer*.

666 Wiley.

667 Sarrazin, F., Pianosi, F., Wagener, T., 2016. Global sensitivity analysis of en-
 668 vironmental models: Convergence and validation. *Environmental Modelling*
 669 & *Software* 79, 135 – 152.

670 Sedighian, S., Kim, S. H., Cho, S. Y., Kim, M., Kim, D., Cha, D., 2015.
 671 Parameter ranking system of indoor radon concentration in South Korea,
 672 case studies: Dokdo island, Yang Pyeong and Nae Gi. *International Journal*
 673 *of Environmental Research* 9 (4), 1233–1236.

674 Smirnov, N., 1939. On the estimation of the discrepancy between empirical
 675 curves of distribution for two independent samples. *Bulletin Mathématique*
 676 *de l'Université de Moscou* 2 (2).

677 Spear, R., Grieb, T., Shang, N., 1994. Parameter uncertainty and interaction
 678 in complex environmental models. *Water Resources Research* 30 (11), 3159–
 679 3169.

680 Stanfill, B., Mielenz, H., Clifford, D., Thorburn, P., 2015. Simple approach to
 681 emulating complex computer models for global sensitivity analysis. *Envi-*
 682 *ronmental Modelling & Software* 74, 140 – 155.

683 Strong, M., Oakley, J., Brennan, A., 2014. Estimating multiparameter partial
 684 expected value of perfect information from a probabilistic sensitivity analy-
 685 sis sample: a nonparametric regression approach. *Medical Decision Making*
 686 34 (3), 311–326.

687 Tang, Y., Reed, P., Wagener, T., van Werkhoven, K., 2007. Comparing sensi-
 688 tivity analysis methods to advance lumped watershed model identification
 689 and evaluation. *Hydrology and Earth System Sciences* 11, 793–817.

690 Van Werkhoven, K., Wagener, T., Tang, Y., Reed, P., 2008. Rainfall character-
 691 istics define the value of streamflow observations for distributed watershed
 692 model identification. *Geophysical Research Letters* 35 (L11403).

693 Van Werkhoven, K., Wagener, T., Tang, Y., Reed, P., 2009. Complexity re-
 694 duction in multiobjective watershed model calibration. *Advances in Water*
 695 *Resources* 32 (8), 1154–1169.

696 Wagener, T., Kollat, J., 2007. Visual and numerical evaluation of hydrologic
 697 and environmental models using the monte carlo analysis toolbox (MCAT).
 698 *Environmental Modelling & Software* 22, 1021–1033.

699 Xiaomeng, S., Jianyun, Z., Chesheng, Z., Yunqing, X., Ming, Y., Chonggang,
 700 X., 2015. Global sensitivity analysis in hydrological modeling: Review of
 701 concepts, methods, theoretical framework, and applications. *Journal of Hy-*
 702 *drology* 523, 739–757.

703 Yang, J., 2011. Convergence and uncertainty analyses in monte-carlo based
 704 sensitivity analysis. *Environmental Modelling & Software* 26 (4), 444–457.

705 Zadeh, F. K., Nossent, J., Sarrazin, F., Pianosi, F., van Griensven, A., Wa-
 706 gener, T., Bauwens, W., 2017. Comparison of variance-based and moment-
 707 independent global sensitivity analysis approaches by application to the
 708 SWAT model. *Environmental Modelling & Software* 91, 210 – 222.

Fig. 1. Example of using a tailored sampling strategy (left) and generic sampling (right) to approximate the PAWN index of input x_1 in a case of $M=3$ input factors. Left (tailored): (a) Input samples used to derive the unconditional output sample YU. These are generated by randomly sampling the entire space of input variability. (b) Input samples used to derive three conditional samples YC_{11} , YC_{12} and YC_{13} . These are generated by fixing x_1 at selected conditioning values (for the sake of clarity, only $n=3$ conditioning values are shown here). (c) Scatter plot of the unconditional (red) and conditional (grey) output samples YU, YC_{11} , YC_{12} and YC_{13} against x_1 . Right (generic): similar to the left hand side but this time the input samples in (d) and (e) are the same. A random subset (highlighted in red) is used to derive YU, and the three subsets obtained by splitting the variability range of x_1 into 3 intervals (grey) are used to derive YC_{11} , YC_{12} and YC_{13} . After sampling, the approximation of the PAWN sensitivity index follows the same steps: (g) unconditional output distribution (red) and the three conditional distributions (grey) when x_1 is fixed to a given value (interval). (h) KS statistic (maximum absolute difference) between the unconditional distribution and each of the three conditional ones, plotted against the conditioning value (centre of the interval).

Fig. 2. Schematic of the steps needed to apply PAWN using a tailored sampling strategy (left) and generic sampling (right). In the latter case, if a generic input/output dataset is already available, the very first step of sampling and model evaluation can be skipped and the subsequent steps applied to the available dataset.

Fig. 3. PAWN indices from generic sample for the three input factors of the Ishigami-Homma function. Each subplot report results for one input factor. The PAWN index is defined as the median KS across conditioning intervals (i.e. Eq. (5) where $\text{stat}=\text{median}$). PAWN indices are approximated using an increasing sample size (N) and increasing number of conditioning intervals (n). For each combination of (N, n) , bootstrapping is used to estimate the 95% confidence interval (vertical line) and mean value (circle) of each PAWN index. Dashed lines show the KS of the dummy parameter computed according to Eq. (6) at each combination of (N, n) . For comparison, the Figure also shows the PAWN indices approximated using the tailored sampling strategy (black diamond).

Fig. 4. PAWN sensitivity indices from generic sample for the 50 input parameters of the SWAT simulation model. The PAWN index is defined as the median KS across conditioning intervals (i.e. Eq. (5) where $\text{stat}=\text{median}$). Bootstrapping is used to estimate the 95% confidence interval (vertical line) and mean value (bar height) of each PAWN index. The red line shows the KS of the dummy parameter computed by Eq. (6). Input parameters are sorted according to their PAWN index values.

	PAWN from generic dataset	Method of Morris & VBSA	Regional Sensitivity Analysis
Ranking of influential inputs	11	11	11
	9	9	32
	32	10	
	10		
	8	32	9
	17	8	8
	2	2	2
	43	43	43
(from Sarrazin et al (2016))			

1st
 2nd
 3rd
 4th

Fig. 5. Comparison between the ranking of influential parameters derived from the PAWN indices and those obtained in Sarrazin et al. (2016) by applying the method of Morris, Variance-Based Sensitivity Analysis (VBSA) and Regional Sensitivity Analysis.

Fig. 6. Effect of the sample size N on the PAWN sensitivity indices approximated from a generic sample. Notice that the results in the bottom panel are the same as in Fig. 4 and are only reported to facilitate comparison. In all panels the input parameters are presented in the same order: this order coincides with their ranking (from most influential to least) in the bottom panel but not necessarily in the others given that the PAWN sensitivity estimates are different. The red line depicts the dummy parameter result.

Fig. 7. Effect of the tuning parameter n (number of conditioning intervals) on the PAWN sensitivity indices approximated from generic sample (sample size $N=5000$). Red crosses are used to mark sensitivity indices whose value is not higher than the KS of the dummy parameter, and hence is within margins of approximation errors.

Fig. 8. Same as in Figure 6 but defining the PAWN index as the mean KS across conditioning intervals, i.e. $\text{stat}=\text{mean}$ in Eq. (5) instead of median.

Fig. 9. Same as in Figure 6 but defining the PAWN index as the maximum KS across conditioning intervals, i.e. $\text{stat}=\max$ in Eq. (5).

Fig. 10. Scatter plots and KS statistics of four selected input parameters of the SWAT model: number 11 is the one consistently ranked as most influential, number 43, 35 and 46 are classified as influential if using the maximum KS as PAWN sensitivity index, while they are not if using the mean or median KS.