Haines, R., Lewis, T., Coon, J. P., & Fanning, N. (2006). Non-Linear Optimization of IEEE802.11e Superframe Configuration. In *2006 IEEE 63rd Vehicular Technology Conference: Proceedings of a meeting held 7-10 May 2006, Melbourne, Australia* (Vol. 3, pp. 1211-1215). (IEEE Vehicular Technology Conference). Institute of Electrical and Electronics Engineers (IEEE).
<https://doi.org/10.1109/VETECS.2006.1683027>

Peer reviewed version

Link to published version (if available):
[10.1109/VETECS.2006.1683027](https://doi.org/10.1109/VETECS.2006.1683027)

[Link to publication record in Explore Bristol Research](#)
PDF-document

University of Bristol - Explore Bristol Research

General rights

This document is made available in accordance with publisher policies. Please cite only the published version using the reference above. Full terms of use are available:
<http://www.bristol.ac.uk/red/research-policy/pure/user-guides/ebr-terms/>

Non-Linear Optimization of IEEE802.11e Super-frame Configuration

Russell Haines, Tim Lewis, Justin Coon, Neil Fanning

Telecommunications Research Laboratory,

Toshiba Research Europe Ltd.,

32, Queen Square, Bristol, BS1 4ND, UK

[Russell.Haines, Tim.Lewis, Justin.Coon, Neil.Fanning]@toshiba-trel.com

Abstract — As the potential data-rates of wireless local area networks (WLANs) continue to rise, the ability of such systems to support a rich set of applications increases. The centralized control functions in the IEEE802.11 family of standards have been developed to enable both data-oriented (browsing, email, etc.) traffic and quality of service (QoS) sensitive traffic to coexist. Balancing the demands of the two types of traffic has, to date, been achieved by algorithms based on experimental, heuristic data. In this paper we present a non-linear optimization theory-based approach for deriving optimum configurations with the IEEE802.11e centralized control functions in mind. The optimization algorithm itself (the “Barrier Method”) is well-known; the challenge in problems such as this is in the formation of the utility function and its constraints, so these are explored in detail. Finally, we show the advantages of this approach over discrete look-up based approaches.

Keywords — Optimization, WLAN, 802.11, HCF, PCF, CFP, CP.

I. INTRODUCTION

Wireless local area networks (WLAN), such as those defined by the IEEE802.11 family of standards, are increasingly being used to support rich multimedia audio/visual (A/V) applications. Such applications have very demanding quality of service (QoS) needs such as guaranteed delay and delay-variance, as well as, typically, higher bandwidth requirements. The best-effort contention-based Distributed Coordination Function (DCF) of the IEEE802.11 standard [1] struggles to support such traffic. The centralized Point Coordination Function (PCF) of the original IEEE802.11 standard and the enhanced Hybrid Coordination Function (HCF) in the IEEE802.11e standard [2] both introduce centralized coordination to allow QoS-sensitive traffic to coexist alongside contention-based data exchanges. However, there is a relative paucity of research on the centralized control functions of IEEE802.11 when compared to the vast body of work available on the DCF and *ad hoc* networking, and this contribution partially redresses this imbalance.

Centralized coordination imposes a time-based repeating super-frame onto the medium (as illustrated in Fig. 1), characterized by the transmission of a broadcast beacon, followed by a contention-free (polled) period (CFP) and then a contention-based access period (CP). The duration of the super-frame (i.e. the beacon and CFP repetition rate) and the

relative size of the CFP to the rest of the super-frame, typically termed CFP_{REP} and CFP_{MAX} , are both configurable by the centralized controller entity located at the Access Point (AP).

The configuration of these parameters determines the success of a given WLAN deployment from the perspective of the polled traffic, the contention-based traffic or both. A badly configured system will fail to deliver the performance that the end-user has the right to expect, irrespective of the headline data rate of the product.

A self-adaptive scheme has been proposed and studied [3]. This scheme selects parameters from pre-defined look-up tables indexed by a quantized number of active polled stations and stepped values for the maximum allowable delay of the applications. The values populating the look-up tables are derived through experimental simulation results, and do not take into account the minimum CFP and CP sizes mandated by the standard [1].

A more flexible and adaptable approach would allow an continuous optimized set of super-frame parameters to be derived; an approach with a more theoretical basis would permit greater confidence in the optimal nature of the values being employed than is possible with experimental results.

The mathematical technique proposed as a candidate solution in this paper is that of non-linear optimization. The various methods within non-linear optimization theory optimize (as the name suggests) any number of variable parameters to provide a stable system solution. Non-linear optimization has been applied to various problem domains within communications, including wireless sensor network access [4] and deriving training sequences for orthogonal frequency division multiplexing (OFDM) systems [5, 6]. We use the barrier method [7] in this work. The success of non-linear optimization approaches is dependant on how well the objective and constraint functions model the behavior under study.

Fig. 1 Super-frame Structure

II. UTILISATION MODEL AND OBJECTIVE FUNCTION

The goal of configuring the super-frame is to try to satisfy both the polled and contending traffic flows. If just one traffic flow were given free rein, this would be at the expense of the other. It is important to guarantee the polled (QoS-sensitive) traffic, but not if it starves the contending traffic. Our approach is to maximize the utilisation of the two phases simultaneously within a number of constraints, such that the two phases' utilizations are traded-off against each other.

To begin with, then, the utilisation expressions of the two phases must be developed; i.e. the efficiency of the allocation of air-time to the different phases. The goal is to develop expressions that indicate how far from the ideal each component is.

Certain assumptions are required even at this high level starting point in order to simplify the mathematics that follows. These include:-

- bit-errors and interference neglected
- no hidden-terminal or capture effect
- no collisions
- no stations are power-saving
- terminals are fully back-logged

The efficiency of each phase can be further decomposed into two factors—the inherent inefficiency in each individual exchange (which scales linearly with the number of exchanges) and the phase inefficiency, comprising any unused-airtime wastage at the end of the phase. We seek to derive, then, two expressions, one for the utilisation of the polled traffic and one for the contending data traffic.

In the case of the polled traffic it is easy to compute how much of the bandwidth is being wasted and aim to minimize that. Each polled exchange incurs the standard inter-frame space penalties, specifically two SIFS periods, as shown in Fig. 2. Hence for a polled exchange, the overhead is simply twice the SIFS duration of the PHY in question.

$$C_a = 2 * SIFS \quad (1)$$

The second factor is the wastage in the CFP caused by it being configured to any size not divisible exactly by the frame exchange duration (in practice the central controller can terminate the CFP early and make this “wasted” period available to the CP).

Fig. 2 Polling Frame Model

Hence, the wastage incurred within the polling period, comprising the wastage per polled-exchange plus whatever surplus remains at the end of the CFP, can be expressed as:

$$V(N_p) = \left(1 - \frac{N_p (C_b - C_a)}{xy} \right) \quad (2)$$

Where C_b is the entire polled exchange duration (ms) and C_a is the polled exchange overhead from (1), and x and y are CFP_{MAX} and CFP_{REP} respectively.

The number of polled terminals, N_p , is a parameter that the AP can reasonably be expected to know as all stations must associate with the AP if polling service is required.

For the contending traffic it is more straightforward to consider and maximize the percentage of the bandwidth that was actually used to transmit useful data. During contention, stations must wait for the DIFS period of silence on the medium (with the 802.11b physical layer, this is 50μs, compared to the SIFS of 10μs). Having reached the end of DIFS, the station backs off for a random number of slots (each of 20μs duration in 11b) drawn from the range [0, CW], where CW begins at 31 (11b again) and can increase as a binary exponential up to the limit 1023. If the medium goes busy during the contention window (the slot-count-down) then the STA will suspend the count down, wait for the medium to go idle for DIFS again, then resume counting from where it left off.

One of the aforementioned assumptions was “no collisions”, and this assumption can be used to simplify the “truncated binary exponential back-off” mechanism by freezing CW at 31, and simply taking a mean CW value of 15.5 (albeit a non-integer value) for every contention. If every contention is assumed to win without any other terminal transmitting during the CW phase (although in reality the probability of seeing another terminal transmit is going to increase with the number of terminals present) then a single DIFS per contention can be assumed.

A final simplification is for the calculations to consider a single “standardized” payload size for the contention-based traffic, corresponding to the mean. The first part of the utilisation expression is the implicit utilisation of a particular exchange, as illustrated in Fig. 3.

Fig. 3 Contending Frame Model

This gives an overhead of:

$$M_s = DIFS + Backoff + SIFS + ACKFrame \quad (3)$$

Then we can incorporate the wastage at the end of each CP. The effective number of contending stations will depend on the traffic level and the total number of contending stations N_c . If we know the approximate packet rate of this traffic, P_r , the effective number of concurrently sending stations will be $y \times P_r \times N_c$. This results in the utilisation for the contention period:

$$L(N_c) = 1 - \frac{y \times P_r \times N_c (H_s - M_s) + y(1-x)}{y(1-x)}$$

Which simplifies to:

$$L(N_c) = \frac{P_r \times N_c (M_s - H_s)}{(1-x)} \quad (4)$$

Where H_s is the entire standardized contended exchange duration (in ms), M_s is the standardized contended exchange overhead (ms) from (3), N_c is the number of contending stations, y is CFP_{REP} and x is CFP_{MAX} .

This expression must be constrained by the frame-generation rate of the traffic, otherwise this becomes almost a “self optimizing” model that will always fill the CP to capacity. We can use the utilisation functions L and V in the following objective function:

$$f_0(x, y) = (1 - L(N_c))^2 + (V(N_p))^2 \quad (5)$$

We use the $1 - L(N_c)$ term since higher values of L correspond to good performance (in contrast high values of V indicate poorer performance), and square both terms to ensure that both are positive and differentiable over the whole domain of interest. Plugging in the expressions for L given in (4) and V from (2) and simplifying gives:

$$f_0(x, y) = \left(1 - \frac{P_r N_c (M_s - H_s)}{1-x}\right)^2 + \left(1 - \frac{N_p (C_b - C_a)}{xy}\right)^2 \quad (6)$$

The possible solutions are constrained in a number of ways. CFP_{MAX} is a ratio of two time periods so must be positive and less than one. CFP_{REP} is bounded by the worst case polling frequency (“delay”, D) specified by the application. Additionally, both the CFP and CP are subject to minimum duration constraints (“ CFP_{MIN} ” and “ CP_{MIN} ” respectively) according to the standard [1]. The CFP has to be at least big enough to contain one polled exchange comprising the largest payload possible in each direction, plus a Beacon and a CF-End. The CP has to be large enough to contain an acknowledged exchange of the largest payload possible.

Mathematically, the problem reduces to an optimization problem over two variables, x and y : Minimize $f_0(x, y)$ from equation (6), subject to the set of constraints:

$$\begin{aligned} CFP_{min} - xy &\leq 0 \\ CP_{min} - (1-x)y &\leq 0 \\ 0 &\leq x \leq 1 \\ 0 &\leq y \leq D \end{aligned} \quad (7)$$

III. NON-LINEAR VECTOR OPTIMIZATION OF MODEL

The barrier method [7] can be used to solve this optimization problem. However, it is desirable to first reformulate the objective function as a function of a single variable that is a vector. For this reformulation, let $\mathbf{z} = (x, y)^T$, and define the length two unit vectors as $\mathbf{e}_1 = (1, 0)^T$ and $\mathbf{e}_2 = (0, 1)^T$. With these definitions in mind, the objective function can be rewritten as follows.

$$f_0(\mathbf{z}) = \left(1 - \frac{\alpha}{1 - \mathbf{e}_1^T \mathbf{z}}\right)^2 + \left(1 - \frac{\beta}{\mathbf{z}^T \mathbf{E} \mathbf{z}}\right)^2 \quad (8)$$

Here $\alpha = P_r N_c (M_s - H_s)$, $\beta = N_p (C_b - C_a)$ and $\mathbf{E} = \mathbf{e}_1 \mathbf{e}_2^T$. In vector notation the constraints can be restated as follows:

$$\begin{aligned} CFP_{min} - \mathbf{z}^T \mathbf{E} \mathbf{z} &\leq 0 & 1^{st} \text{ constraint} \\ CP_{min} - \mathbf{e}_2^T \mathbf{z} + \mathbf{z}^T \mathbf{E} \mathbf{z} &\leq 0 & 2^{nd} \text{ constraint} \\ \mathbf{e}_1^T \mathbf{z} - 1 &\leq 0 & 3^{rd} \text{ constraint, upper bound} \\ -\mathbf{e}_1^T \mathbf{z} &\leq 0 & 3^{rd} \text{ constraint, lower bound} \\ \mathbf{e}_2^T \mathbf{z} - D &\leq 0 & 4^{th} \text{ constraint, upper bound} \\ -\mathbf{e}_2^T \mathbf{z} &\leq 0 & 4^{th} \text{ constraint, lower bound} \end{aligned}$$

The constants are determined by the physical layer under consideration and the characteristics of the traffic flows.

M_s standardized data exchange overhead, ms

H_s standardized data exchange, ms

C_a polled exchange overhead, ms

C_b polled exchange duration, ms

N_c number of data stations

CFP_{min} CFP_{MIN} , ms

CP_{min} CP_{MIN} , ms

$D \in \{\dots\}$ polling rates under consideration

$N_p \in \{\dots\}$ numbers of polling stations considered

P_r packet generation rate for contending traffic

This problem can now be solved using standard convex optimization techniques such as the barrier method [7]; however, the objective function is not convex so feasible starting points must be determined to pick the appropriate

local minima (there are never more than three such points and the three initial values we use will always locate the desired one). By examining the inequality constraints of the original problem it is possible to find feasible starting points x_0 and y_0 that can be used to initialize the barrier method. Observe the following two inequalities:

$$CFP_{\min} \leq xy \quad CP_{\min} \leq (1-x)y$$

$$= y - xy$$

These are obtained by rearranging the first two inequalities of the original problem statement. Solving the second inequality for xy enables the composite inequality to be written as: $CFP_{\min} \leq xy \leq y - CP_{\min}$

Thus, for a given $y = y_0$, a feasible $x = x_0$ can be taken from the interval:

$$x_0 \in \left(\frac{CFP_{\min}}{y}, 1 - \frac{CP_{\min}}{y} \right) \quad (9)$$

and the following feasible starting point constraint must be met.

$$CFP_{\min} > y_0 - CP_{\min} \quad (10)$$

IV. APPLICATION OF MODEL

The assumptions and parameters used in the aforementioned static self-adaptive scheme [3] can be adopted by this model to give some concrete values. These parameters include an 802.11b MAC/PHY configuration (affecting IFS times and the like), with ten data stations contending for access in the CP. These parameters are given in Table 1 along with the resulting concrete values for the constants in the expressions developed in the previous sections.

Feasible starting points can then be considered - the starting point constraint in (10) can be met for these values when, for example, $CFP_{\min} = 39.922$, $CP_{\min} = 21.404$ and $y_0 = 48$.

Table 1: Model Parameters

Parameter	Value	Parameter	Value
Slot	0.02ms	PIFS	0.03ms
SIFS	0.01ms	DIFS	0.05ms
MAC Header	28 bytes	PLCP Header/Preamble	0.192ms
Mean data MSDU	1000 bytes	Mean data rate	7.5 fps
A/V MSDU	200 bytes	A/V data rate	64 kbps, 1s on, 1.35s off
Data rate	2Mbps	Control rate	1Mbps
Beacon	160 bytes	ACK	14 bytes
M_s	0.674 ms	H_s	4.978 ms
C_a	0.02 ms	C_b	2.228 ms
N_c	10 stations	N_p	{2, 4, ..., 20}
$CFP_{\min}$	39.922 ms	$CP_{\min}$	21.404 ms
P_r	0.0075 s^{-1}	D	{75, 87.5, 100, 112.5, ..., 200} ms

The barrier method was used to find optimal values of x and y for the different combinations of D and N_p given above. As mentioned previously the objective is not in general convex, for certain values of the parameters D and N_p it can have up to three local minima. The particular minimum that the algorithm converges on depends on the initial values, and is particularly sensitive to the value of the x component. We keep the initial y value constant and close to its maximum of D . The three local minima were discovered using the following set of initial x values:

1. $1.2*(CFP_{\min})/y$
2. $0.5*(1-CP_{\min}-CFP_{\min})/y$
3. $0.8*(1-(CP_{\min}-CFP_{\min})/y)$

The first of these is a point near the lower end of the feasible set, the second a point in the middle and the third a point towards the top end of the feasible set for x . For many values of D and N_p , all of these local minima were found to be identical, indicating that the local minimum is a global minimum. In the case where more than one local minima was found the objective function was evaluated at each and the true minimum chosen. The minimum values obtained are illustrated in Fig. 4 and Fig. 5, and listed in Table 2.

Fig. 4 CFP_{MAX} Optimization Results

Fig. 5 CFP_{REP} Optimization Results

Table 2: Optimum CFP_{MAX} and CFP_{REP} values

N_v	$T_{th} = 200ms$		$T_{th} = 150ms$		$T_{th} = 100ms$		$T_{th} = 75ms$	
	CFP_{MAX}	CFP_{REP}	CFP_{MAX}	CFP_{REP}	CFP_{MAX}	CFP_{REP}	CFP_{MAX}	CFP_{REP}
2	0.293	173	0.487	126	0.399	100	0.532	75
4	0.246	184	0.528	130	0.502	91	0.532	75
6	0.242	181	0.569	135	0.520	90	0.532	75
8	0.244	182	0.412	125	0.538	89	0.532	75
10	0.241	184	0.353	132	0.519	90	0.532	75
12	0.453	168	0.443	126	0.510	78	0.532	75
14	0.380	165	0.604	139	0.504	85	0.532	75
16	0.520	162	0.507	92	0.399	100	0.532	75
18	0.346	148	0.506	108	0.399	100	0.532	75
20	0.385	152	0.482	125	0.399	100	0.532	75

The optimum values of CFP_{MAX} are fairly variable, especially for larger values of D and the smaller values of N_p . This variability seems to occur mainly when the objective is most flat: in that it does not vary much over a wide range of CFP_{MAX} values. This means the instability happens in exactly the situations where choosing a precise value of CFP_{MAX} is least important. The CFP_{REP} optima tend to be close to the maximum D , especially for smaller D where the constraints do not permit much variation anyway. For larger D , the optimum values are significantly smaller than D , this is in line with the fact that there is much more potential to fit the polled and contention periods within a smaller repetition time.

The OPNETTM simulation tool has been used to model a centrally coordinated IEEE802.11 system with the parameters given in Table 1. Simulations were run for a variety of CFP_{REP} values, providing throughput, delay and delay jitter values in each case for both polled and contending traffic. By examining these results, it is possible to identify several points of interest, such as the smallest CFP_{MAX} value at which required throughput threshold for polled traffic can be achieved, the largest CFP_{MAX} value at which the required throughput threshold for contending traffic can be maintained, and the resulting delay characteristics in each case. The CFP_{MAX} values predicted by the optimization process fall within these upper and lower bounds for CFP_{MAX} , justifying the values obtained.

By means of comparison against the benchmark for these preliminary results, Table 3 gives the upper and lower bounds from the simulation alongside the values predicted by both the optimization method and the benchmark results [3]. Whilst the comparative benchmark results consistently sit toward the upper end of the range established by these simulation results, the values derived by the optimization approach are predominantly in the middle of the observed range of possible CFP_{MAX} values.

Table 3: Derived CFP_{MAX} vs. Simulation Results (12 Station case)

Delay /ms	Simulation		Benchmark [3]	Optimization (Table 2)
	Lower	Upper		
75	0.55	0.75	0.7	0.532
100	0.45	0.55	0.7	0.51
150	0.3	0.45	0.6	0.443
200	0.3	0.5	0.6	0.453

V. CONCLUSIONS

We have presented an application of non-linear optimization that fine-tunes the structure of the super-frame in centralized WLAN applications. This is of particular interest because the latest WLAN data rates make supporting A/V traffic attractive, but centralized control functions are then required to meet the strict QoS requirements.

We have focused on the objective function and the constraints that bound it, along with the operations required to reach the standard form amenable to optimization by the Barrier Method.

The previously published work in this area [3] has the significant limitation that the minimum sizes of the CFP and CP are not taken in to account, which would severely hinder its usage in a real implementation. This work offers a more viable solution for that reason alone. In addition to this, our preliminary results show agreement between simulated system behavior and the optimal values predicted by the non-linear optimization approach.

The optimized super-frame configurations are applicable for a range of delivery delay requirements and numbers of stations, and are fixed for a particular physical layer and for given application traffic characteristics; both of these aspects are either known or can be bounded at design time.

In terms of future work, further simulation to consider situations outside of the stated assumptions (e.g. with more realistic collisions and back-offs, or when terminals are not fully backlogged) would be valuable in justifying the superframe configurations under more realistic conditions. The utility function can be further developed to incorporate a bias term to favor either CFP or CP, depending on the priority of the system. The heterogeneity and time-varying nature of the application traffic profiles must also be considered. Lastly, more detailed comparisons of the performance of this approach against the performance of other published works are required, along with complexity and performance analysis of the dynamic re-optimization of revised utility functions when the parameters change.

REFERENCES

- [1] IEEE (Institute of Electrical and Electronics Engineers), "IEEE Standard 802.11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications," 1999.
- [2] IEEE (Institute of Electrical and Electronics Engineers), "IEEE Standard 802.11e - Part 11 Amendment 8: Medium Access Control (MAC) Quality of Service Enhancements," 2005.
- [3] C. Li, M. Li, and X. Cai, "A study of self-adaptive transmission for integrated voice and data services over an IEEE 802.11 WLAN," *15th IEEE International Symposium on Personal, Indoor and Mobile Radio Communications, 2004. PIMRC 2004.*, vol. 3, pp. 1922 - 1926, 2004.
- [4] B. Krishnamachari and F. Ordonez, "Analysis of energy-efficient, fair routing in wireless sensor networks through non-linear optimization," *IEEE 58th Vehicular Technology Conference, 2003. VTC 2003-Fall.*, vol. 5, pp. 2844 - 2848, 2003.
- [5] J. Coon and M. Sandell, "Designing Unique Words for Near-Optimal Training in Single-Carrier Block Transmission Systems," *IEEE Transactions on Signal Processing (to appear)*, 2005.
- [6] M. Sandell and J. Coon, "Near-optimal training sequences for MIMO OFDM systems with nulled subcarriers," *IEEE Globecom '05*, 2005.
- [7] S. Boyd and L. Vandenberghe, *Convex Optimisation*: Cambridge University Press, 2004.